




TTL Control Logic

SPECIFICATIONS

Input Frequency Range:	2.0 - 8.0 GHz
Switch Type:	SP3T
Insertion Loss:	3.2 dB Max
Isolation:	55 dB Min
VSWR:	1.60:1
Input Power:	200 mw (23 dBm)
Switching Time:	100 nsec
Driver:	Schottkey TTL
Voltage/Current Required:	+5 Vdc @ +70 mA, Typical -5 Vdc @ -50 mA, Typical
Individual TTL Control Logic:	Logic "0" (-0.3V to +0.8V) = ON Logic "1" (+2.0V to +5.0V) = OFF

L1	L2	L3	IN-J1	IN-J2	IN-J3
0	1	1	Insertion Loss	Isolation	Isolation
1	0	1	Isolation	Insertion Loss	Isolation
1	1	0	Isolation	Isolation	Insertion Loss

PULSAR MICROWAVE CORPORATION

PULSAR MICROWAVE CORPORATION
48 INDUSTRIAL WEST, CLIFTON NJ 07012
TEL: 973-779-6262 FAX: 973-779-2727
WWW.PULSARMICROWAVE.COM

DESCRIPTION :

Absorptive RF/Microwave Switch

MODEL NO. :

SW3AD-27

DIMENSIONS ARE IN INCHES
DECIMAL TOLERANCE:
2 PLACE ± .02
3 PLACE ± .010

SIZE
A

CAGE CODE :
0HR85

REV CODE :

170201

SCALE : N / A

ALL SPECIFICATIONS ARE SUBJECT TO
CHANGE WITHOUT NOTICE AT ANY TIME

SHEET 1 OF 1