



SPECIFICATIONS

Input Frequency Range:	0.04 - 8.0 GHz
Switch Type:	SP8T
Insertion Loss:	4.0 dB Max
Isolation:	60 dB Min
VSWR:	2.00:1
Input Power:	200 mw (23 dBm)
Switching Time:	100 nsec
Driver:	Schottkey TTL
Voltage/Current Required:	+5 Vdc @ +120 mA, Typical -5 Vdc @ -50 mA, Typical
Individual TTL Control Logic:	Logic "0" (-0.3V to +0.8V) = ON Logic "1" (+2.0V to +5.0V) = OFF

TTL Control Logic

When L(1 - 8) = TTL LOW, Output(1 - 8) = Loss
 When L(1 - 8) = TTL HIGH, Output (1 - 8) = Isolation

PULSAR MICROWAVE CORPORATION

PULSAR MICROWAVE CORPORATION
 48 INDUSTRIAL WEST, CLIFTON NJ 07012
 TEL: 973-779-6262 FAX: 973-779-2727
 WWW.PULSARMICROWAVE.COM

DESCRIPTION :

Reflective RF/Microwave Switch

MODEL NO. :

SW8RD-14

DIMENSIONS ARE IN INCHES
 DECIMAL TOLERANCE:
 2 PLACE ± .02
 3 PLACE ± .010

SIZE
A

CAGE CODE :
0HR85

REV CODE :
170201

SCALE : N / A

ALL SPECIFICATIONS ARE SUBJECT TO
 CHANGE WITHOUT NOTICE AT ANY TIME

SHEET 1 OF 1