




SPECIFICATIONS

Frequency Range:	10 - 1000 MHz
Isolation:	25 dB Min
Insertion Loss:	0.5 dB Max
Current ¹ :	1000 mA Max
Power:	5 Watts Max
Voltage:	100 Vdc Max
VSWR:	1.20:1 Max

Notes:

- Higher current and isolation requirements available.

PIN-OUT TABLE

RF In (DC Blocked):	1
RF/DC Output:	2
DC In (Bias):	Feed Thru Pins
Ground:	Housing

PULSAR MICROWAVE CORPORATION

PULSAR MICROWAVE CORPORATION
48 INDUSTRIAL WEST, CLIFTON NJ 07012
TEL: 973-779-6262 FAX: 973-779-2727
WWW.PULSARMICROWAVE.COM

DESCRIPTION :

Bias Tee

MODEL NO. :

BT-20-410F

DIMENSIONS ARE IN INCHES
DECIMAL TOLERANCE:
2 PLACE ± .02
3 PLACE ± .010

SIZE
A

CAGE CODE :
0HR85

REV CODE :
160108

SCALE : N / A

ALL SPECIFICATIONS ARE SUBJECT TO
CHANGE WITHOUT NOTICE AT ANY TIME

SHEET 1 OF 1