



SPECIFICATIONS

Frequency Range:	0.5 - 1.0 GHz
Coupling:	6.0 ± 1.00 dB
Insertion Loss ¹ :	0.20 dB Max
Coupling Flatness:	± 0.60 dB Max
Directivity:	22 dB Min
VSWR:	1.15:1 Max
Power Input:	50 Watts Max
Power Reflected:	4 Watts Max
Power Peak:	3 Kilowatts Typ
Connector Type:	N

Notes:

- Device tested in a 50 Ohm system.
- Does not include coupling loss.

PULSAR MICROWAVE CORPORATION

PULSAR MICROWAVE CORPORATION
48 INDUSTRIAL WEST, CLIFTON NJ 07012
TEL: 973-779-6262 FAX: 973-779-2727
WWW.PULSARMICROWAVE.COM

DESCRIPTION :

Directional Coupler

MODEL NO. :

CS06-01-436/3N

DIMENSIONS ARE IN INCHES
DECIMAL TOLERANCE:
2 PLACE $\pm .02$
3 PLACE $\pm .010$

SIZE
A

CAGE CODE :
0HR85

REV CODE :
170130

SCALE : N / A

ALL SPECIFICATIONS ARE SUBJECT TO
CHANGE WITHOUT NOTICE AT ANY TIME

SHEET 1 OF 1