



## SPECIFICATIONS

Frequency Range:	2.6 - 5.2 GHz
Coupling:	20.0 ± 1.25 dB
Insertion Loss <sup>1</sup> :	0.20 dB Max
Coupling Flatness:	± 0.75 dB Max
Directivity:	20 dB Min
VSWR:	1.25:1 Max
Power Input:	50 W Max
Power Reflected:	50 W Max
Power Peak:	3 kW Typ
Connector Type:	SMA

### Notes:

Device tested in a 50 Ohm system

- Does not include coupling loss.

**PULSAR** MICROWAVE CORPORATION

PULSAR MICROWAVE CORPORATION  
48 INDUSTRIAL WEST, CLIFTON NJ 07012  
TEL: 973-779-6262 FAX: 973-779-2727  
WWW.PULSARMICROWAVE.COM

DESCRIPTION :

Directional Coupler

MODEL NO. :

CS20-07-435/1

DIMENSIONS ARE IN INCHES  
DECIMAL TOLERANCE:  
2 PLACE ± .02  
3 PLACE ± .010

SIZE  
A

CAGE CODE :  
0HR85

REV CODE :  
170130

SCALE : N / A

ALL SPECIFICATIONS ARE SUBJECT TO  
CHANGE WITHOUT NOTICE AT ANY TIME

SHEET 1 OF 1