



SPECIFICATIONS

| | |
|-------------------------------|----------------|
| Frequency Range: | 7.5 - 16.0 GHz |
| Coupling: | 20.0 ± 1.25 dB |
| Insertion Loss ¹ : | 0.50 dB Max |
| Coupling Flatness: | ± 0.75 dB Max |
| Directivity: | 15 dB Min |
| VSWR: | 1.40:1 Max |
| Power Input: | 50 W Max |
| Power Reflected: | 50 W Max |
| Power Peak: | 3 kW Typ |
| Connector Type: | SMA |

Notes:

Device tested in a 50 Ohm system.

- Does not include coupling loss.

PULSAR MICROWAVE CORPORATION

PULSAR MICROWAVE CORPORATION
48 INDUSTRIAL WEST, CLIFTON NJ 07012
TEL: 973-779-6262 FAX: 973-779-2727
WWW.PULSARMICROWAVE.COM

DESCRIPTION :

Directional Coupler

MODEL NO. :

CS20-13-435/3

DIMENSIONS ARE IN INCHES
DECIMAL TOLERANCE:
2 PLACE ± .02
3 PLACE ± .010

SIZE
A

CAGE CODE :
0HR85

REV CODE :
170130

SCALE : N / A

ALL SPECIFICATIONS ARE SUBJECT TO
CHANGE WITHOUT NOTICE AT ANY TIME

SHEET 1 OF 1