

Coaxial Directional Coupler

50Ω 5 to 1200 MHz


Maximum Ratings

Operating Temperature	-40°C to 85°C
Storage Temperature	-55°C to 100°C
Permanent damage may occur if any of these limits are exceeded.	

Coaxial Connections

INPUT	1
OUTPUT	2
COUPLED	3

Outline Drawing



Outline Dimensions (inch/mm)

A	B	C	D	E	F	G
.74	.90	.54	.50	.04	.16	.29
18.80	22.86	13.72	12.70	1.02	4.06	7.37
H	J	K	L	M	N	wt
.37	--	.122	.496	.106	.122	grams
9.40	--	3.10	12.60	2.69	3.10	20.0

Features

- very flat coupling
- very broad, multi-octave
- all welded construction
- protected by U.S. Patents 6,140,887 & 6,784,521 & 6,790,049

Applications

- VHF/UHF
- communications receivers & transmitters
- cellular
- instrumentation




Directional Coupler Electrical Specifications (T_{AMB} = 25°C)

FREQ. (MHz)	COUPLING (dB)		MAINLINE LOSS ¹ (dB)						DIRECTIVITY (dB)						VSWR (:1)	POWER INPUT, W		
f _L -f _U	Nom.	Typ. Flatness	L	M	U	L	M	U	L	M	U	L	M	U	Typ.	L	MU	Max. Max.
5-1200	13.0±0.5	±0.3	06	0.9	0.7	1.1	0.9	1.5	21	18	19	15	15	10	1.15	0.5	1.0	


L = low range [f_L to 10 f_L] M = mid range [10 f_L to f_U/2] U = upper range [f_U/2 to f_U]
1. Mainline loss includes theoretical power loss at coupled port.

Typical Performance Data

Frequency (MHz)	Mainline Loss (dB) In-Out	Coupling (dB) In-Cpl	Directivity (dB)	Return Loss (dB)		
				In	Out	Cpl
5.00	0.67	12.93	21.86	22.28	30.20	24.37
10.00	0.63	12.92	21.79	22.90	33.04	24.96
50.00	0.64	12.94	21.62	23.33	35.18	25.41
100.00	0.65	12.97	21.36	23.44	34.61	25.60
200.00	0.67	13.00	20.75	23.69	32.95	25.93
400.00	0.72	13.06	19.10	24.38	30.15	26.19
500.00	0.75	13.10	18.21	24.74	29.05	25.88
800.00	0.90	13.20	15.71	24.52	27.13	24.26
1000.00	1.05	13.22	14.27	23.46	26.43	23.13
1200.00	1.19	13.34	12.99	21.92	25.81	22.53



Electrical Schematic



* ELECTRICAL SCHEMATIC IS FOR DIRECTIONAL COUPLER WITH INTERNAL TRANSFORMATION THAT ROUTES DC FROM RF PORTS TO GROUND.


Notes

- A. Performance and quality attributes and conditions not expressly stated in this specification document are intended to be excluded and do not form a part of this specification document.
B. Electrical specifications and performance data contained in this specification document are based on Mini-Circuit's applicable established test performance criteria and measurement instructions.
C. The parts covered by this specification document are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCStore/terms.jsp



www.minicircuits.com P.O. Box 350166, Brooklyn, NY 11235-0003 (718) 934-4500 sales@minicircuits.com

ZX30-13-4-S+



CASE STYLE: FL905

Connectors Model
SMA ZX30-13-4-S+

+RoHS Compliant

The +Suffix identifies RoHS Compliance. See our web site for RoHS Compliance methodologies and qualifications

REV. L
M171494
ED-10213A/3
ZX30-13-4-S+
WZ/TD/CP/AM
181213
Page 1 of 1