
Surface Mount

Bandpass Filter

SXBP-1200+

50Ω 800 to 1800 MHz



CASE STYLE: HF1317

Maximum Ratings

Operating Temperature	-40°C to 85°C
Storage Temperature	-55°C to 100°C
RF Power Input	0.5W Max.

Permanent damage may occur if any of these limits are exceeded.

Pin Connections

INPUT	1
OUTPUT	8
GROUND	2, 3, 4, 5, 6, 7

Features

- wideband, 800 to 1800 MHz
- flat group delay @ passband, 1 nsec typ.
- shielded case
- aqueous washable


Applications

- receivers/transmitters
- wireless communication systems
- harmonic rejection

+RoHS Compliant

The +Suffix identifies RoHS Compliance. See our web site for RoHS Compliance methodologies and qualifications

Outline Drawing




Outline Dimensions (inch / mm)

A	B	C	D	E	F
.44	.74	.19	.200	.07	.060
11.18	18.80	4.83	5.08	1.78	1.52

G	H	J	K	L	M	wt.
.040	.660	.200	.470	.055	.060	grams
1.02	16.76	5.08	11.94	1.40	1.52	3.0

Demo Board MCL P/N: TB-368
Suggested PCB Layout (PL-230)



NOTE:
1. TRACE WIDTH IS SHOWN FOR FR4 WITH DIELECTRIC THICKNESS: .025"±.002". COPPER: 1/2 OZ. EACH SIDE. FOR OTHER MATERIALS TRACE WIDTH MAY NEED TO BE MODIFIED.
2. BOTTOM SIDE OF THE PCB IS CONTINUOUS GROUND PLANE.


DENOTES PCB COPPER LAYOUT WITH SMOBC (SOLDER MASK OVER BARE COPPER)

DENOTES COPPER LAND PATTERN FREE OF SOLDER MASK


Bandpass Filter Electrical Specifications (T_{AMB} = 25°C)

CENTER FREQ. (MHz)	PASSBAND (MHz) (Loss < 2dB)	STOPBANDS (MHz)				VSWR (:1)		
		Loss > 20dB		Loss 30dB Typ.		Passband		Stopband
Fc	F1 - F2	F3	F4	F5	F6	Typ.	Max.	Typ.
1200	800 - 1800	535	2220	530	2250 - 5000	1.5	2.1	20

Typical Frequency Response




Functional Schematic




Typical Performance Data at 25°C

Frequency (MHz)	Insertion Loss (dB) x̄	Insertion Loss (dB) σ	Return Loss (dB)	Frequency (MHz)	Group Delay (nSec)
1.0	72.93	0.47	0.00	800.0	1.66
530.0	38.97	2.80	0.49	850.0	1.49
535.0	34.49	2.93	0.51	900.0	1.37
570.0	15.37	0.93	0.88	950.0	1.29
600.0	7.18	0.56	2.18	1000.0	1.23
620.0	3.81	0.35	4.23	1050.0	1.19
650.0	1.61	0.13	8.35	1150.0	1.14
800.0	0.67	0.02	17.38	1200.0	1.13
1000.0	0.77	0.01	13.11	1250.0	1.13
1200.0	0.79	0.01	13.92	1300.0	1.13
1500.0	0.97	0.04	14.26	1350.0	1.14
1800.0	1.23	0.06	25.74	1400.0	1.15
1970.0	3.72	0.83	6.44	1500.0	1.19
2030.0	8.79	1.47	3.08	1600.0	1.27
2100.0	16.46	1.72	1.67	1650.0	1.32
2220.0	32.60	2.60	1.02	1700.0	1.39
2250.0	36.64	3.50	0.96	1750.0	1.48
5000.0	32.11	1.21	0.98	1800.0	1.63


SXBP-1200+
INSERTION LOSS



SXBP-1200+
RETURN LOSS



SXBP-1200+
GROUP DELAY



Notes
A. Performance and quality attributes and conditions not expressly stated in this specification document are intended to be excluded and do not form a part of this specification document.
B. Electrical specifications and performance data contained in this specification document are based on Mini-Circuit's applicable established test performance criteria and measurement instructions.
C. The parts covered by this specification document are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCLStore/terms.jsp