# **RF Transformer**

 $50\Omega$ 

0.03 to 20 MHz

### T36-1-KK81+ T36-1-KK81



#### CASE STYLE: KK81

+RoHS Compliant The +Suffix identifies RoHS Compliance. See our web site for RoHS Compliance methodologies and qualifications

INPUT RETURN LOSS

FREQUENCY (MHz)

0.1

#### **Maximum Ratings**

Operating Temperature	-20°C to 85°C
Storage Temperature	-55°C to 100°C
RF Power	0.25W
DC Current	30mA
Permanent damage may occur if any	of these limits are exceeded

#### **Pin Connections**

PRIMARY DOT	4
PRIMARY	6
SECONDARY DOT	3
SECONDARY	1
SECONDARY CT	_
NOT USED	2,5

### **Features**

- good return loss
- also available with plug-in (X65) and flat-pack (W38) leads

#### **Applications**


- amateur radio
- · impedance matching

## **Transformer Electrical Specifications**

Ω <b>RATIO</b> (Secondary/Primary)	FREQUENCY (MHz)	INSERTION LOSS*		
		3 dB MHz	2 dB MHz	1 dB MHz
36	0.03-20	0.03-20	0.05-10	0.1-5

<sup>\*</sup>Insertion Loss is referenced to mid-band loss, 0.4 dB typ.

#### **Outline Drawing**




#### Outline Dimensions (inch )


<b>A</b> . <b>30</b> 7.62	.27	.23	.010	.042	.020	.100	.05	J .05 1.27
.020	.036							wt grams
0.51	0.91	6.60	14.61	15.24	3.18	1.27	2.54	0.50

#### FREQUENCY INSERTION

(MHz)	LOSS (dB)	R. LOSS (dB)	
0.03	2.44	6.98	
0.05	1.60	9.75	
0.05	1.50	10.28	
0.10	0.89	15.22	
0.20	0.69	19.88	
0.27	0.67	20.32	
0.47	0.55	24.87	
2.17	0.38	16.92	
4.66	0.50	10.04	
20.00	2.58	1.81	

**Typical Performance Data** 





- A. Performance and quality attributes and conditions not expressly stated in this specification document are intended to be excluded and do not form a part of this specification document. B. Electrical specifications and performance data contained in this specification document are based on Mini-Circuit's applicable established test performance criteria and measurement ins C. The parts covered by this specification document are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively "Standard Terms"): Purphasers of this part Electrical specifications and performance data contained in this specification document are based on Mini-Circuit's applicable established test performance criteria and measurement instructions.

  The parts covered by this specification document are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCLStore/terms.jsp

100

10