# Coaxial Amplifier

## ZHL-4240+

Medium High Power 600 to 4200 MHz 50Ω

### The Big Deal

- Wideband, 600 to 4200 MHz
- High gain, 39 dB
- Extremely flat gain, ±1.3 dB
- High IP3, +38 dBm





### Product Overview

Mini-Circuits' ZHL-4240+ is a medium-power connectorized amplifier supporting a wide range of applications from 600 to 4200 MHz, such as test instrumentation, SatCom, and mobile communications systems, including those operating in the new telecom Band 71 allocation (617 to 698 MHz). This model provides +31 dBm output power at saturation and extremely flat gain (39 ±1.3 dB) across its full bandwidth, making it ideal for systems where consistent performance across frequency is required. The amplifier operates on a 15V DC supply and comes housed in compact aluminum alloy case (7.00 x 3.25 x 2.13") with SMA connectors, built-in bracket for mounting, and an optional heat sink for efficient cooling.

### **Kev Features**

Feature	Advantages					
Wideband, 600 to 4200 MHz	One amplifier supports a broad range of system and test lab applications. Extended bandwidth down to 600 MHz supports new telecom Band 71 allocation (617 to 698 MHz)					
High gain, 39 dB	Reduces the number of gain stages, lowering component count and overall system cost.					
Excellent gain flatness, ±1.3 dB	Provides consistent performance across frequency, minimizing the need for external equalizing networks in wideband applications.					
Medium output power, +31 dBm P3dB	Supports a wide range of power requirements.					
High OIP3, +38 dBm	Provides highly linear performance with excellent sensitivity and two-tone spur-free dynamic range.					

- A Performance and quality attributes and conditions not expressly stated in this specification document are intended to be excluded and do not form a part of this specification document. B. Electrical specifications and performance data contained in this specification document are based on Mini-Circuit's applicable established test performance criteria and measurement instructions. C. The parts covered by this specification document are subject to Mini-Circuit's standard limited warranty and terms and conditions (collective), "Standard Terms"), Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuit's website at www.minicircuits.com/MCLStore/terms.jsp



Notes

# Coaxial Amplifier

## ZHL-4240+

#### 50Ω Medium High Power 600 to 4200 MHz

#### **Features**

- wideband, 600 to 4200 MHz
- high IP3, +38 dBm typ.
- high gain, 39 dB min.

#### **Applications**

- communication systems
- satellite dist./GPS/PCS
- instrumentation
- laboratory



ZHL-4240X+

CASE STYLE: U36

Connectors Model ZHL-4240+ SMA SMA ZHL-4240X+

+RoHS Compliant

The +Suffix identifies RoHS Compliance. See our web site for RoHS Compliance methodologies and qualifications

#### Electrical Specifications at 25°C

Parameter	Condition (MHz)	Min.	Тур.	Max.	Units
Frequency Range		600	—	4200	MHz
Gain	600-4200	39	42	47	dB
Gain Flatness	600-4200	—	±1.3	±1.8	dB
Output Power at 1dB compression*	600-4200	+28	+30	—	dBm
Output Power at 3dB compression**	600-4200	+29	+31	—	dBm
Noise Figure	600-4200	—	8.0	—	dB
Output third order intercept point	600-4200	—	+38	—	dBm
Input VSWR	600-4200	—	—	2.5	:1
Output VSWR	600-4200	—	—	2.5	:1
DC Supply Voltage		_	15	_	V
Supply Current		_		1.0	А

Open load is not recommended, potentially can cause damage.

With no load derate max. input power by 20 dB.

+27 dBm at 3700-4200 MHz

\*\* +28 dBm at 3700-4200 MHz

Alternative heat sinking and heat removal must be provided by the user to limit maximum base-plate temperature to 65°C, in order to ensure proper performance. For reference, this requires thermal resistance of user's external heat sink to be 1.3°C/W max.

#### **Maximum Ratings**

Parameter	Ratings				
Operating Temperature	-20°C to 65°C				
Storage Temperature	-55°C to 100°C				
DC Voltage	+20V				
Input RF Power (no damage)	-5 dBm				

Permanent damage may occur if any of these limits are exceeded.

Notes

A Performance and quality attributes and conditions not expressly stated in this specification document are intended to be excluded and do not form a part of this specification document. B. Electrical specifications and performance data contained in this specification document are based on Mini-Circuit's applicable established test performance criteria and measurement instructions. C. The parts covered by this specification document are subject to Mini-Circuit's standard limited warranty and terms and conditions (collectived), "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuit's website at www.minicircuits.com/MCLStore/terms.jsp



**ZHL-4240+** 

#### **Outline Drawing for models with heatsink**



#### Outline Dimensions (inch)

S w	S	R	Q	Р	N	Μ	L	K	J	н	G	F	E	D	С	В	Α
3 grams	2.23	6.00	.50	.125	2.23	1.13	.63	.88	.73	.156	2.500	.38	6.500	.25	2.13	3.25	7.00
900	56.64	152.40	12.70	3.18	56.64	28.70	16.00	22.35	18.54	3.96	63.50	9.65	165.10	6.35	54.10	82.55	177.80

\*600 grams without heatsink

Notes
 A. Performance and quality attributes and conditions not expressly stated in this specification document are intended to be excluded and do not form a part of this specification document.
 B. Electrical specifications and performance data contained in this specification document are based on Mini-Circuit's applicable established test performance criteria and measurement instructions.
 C. The parts covered by this specification document are subject to Mini-Circuit standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCLStore/terms.jsp



## Typical Performance Data/Curves

FREQUENCY (MHz)	GAIN (dB)	DIRECTIVITY (dB)	VSWR (:1)		POUT at 1 dB COMPR. (dBm)	POUT at 3 dB COMPR. (dBm)	NOISE FIGURE (dB)	IP3 (dBm)
	15V	15V	IN	OUT	15V	15V	15V	15V
600	44.37	50.13	1.53	1.50	31.45	31.91	8.03	48.11
950	42.33	66.82	1.47	1.75	31.74	31.65	7.71	46.30
1200	41.86	73.44	1.50	2.02	31.68	31.74	7.64	45.16
1450	42.94	61.55	1.46	2.23	31.11	30.91	7.82	41.23
1700	42.88	53.56	1.34	1.88	30.20	30.43	7.76	41.89
1950	42.31	56.25	1.20	1.68	30.30	31.36	7.82	49.01
2200	41.69	61.87	1.11	1.61	30.92	32.04	7.71	47.98
2450	42.63	60.47	1.12	1.62	30.94	31.70	7.87	44.99
2700	42.44	60.33	1.19	1.88	31.93	32.09	8.08	45.51
2950	42.74	70.24	1.21	2.00	31.01	32.06	8.15	53.12
3200	42.34	49.82	1.08	2.04	32.03	32.40	7.88	47.31
3450	41.71	54.55	1.34	1.98	32.65	32.59	8.03	47.97
3700	42.00	50.76	1.34	1.73	31.82	32.14	8.22	48.81
3950	42.15	50.28	1.25	1.24	30.66	31.30	8.32	45.68
4200	41.78	45.95	1.25	1.51	29.13	29.78	8.54	39.05
4200	41.78	45.95	1.25	1.51	29.13	29.78	8.54	39.05













Notes

- Notes
  A. Performance and quality attributes and conditions not expressly stated in this specification document are intended to be excluded and do not form a part of this specification document.
  B. Electrical specifications and performance data contained in this specification document are based on Mini-Circuit's applicable established test performance criteria and measurement instructions.
  C. The parts covered by this specification document are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the refits and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuit's website at www.minicircuits.com/MCLStore/terms.jsp

### Mini-Circuits