Surface Mount **Directional Coupler**

 75Ω

5 to 2000 MHz

Features

• wideband, 5 to 2000 MHz

· leads for excellent solderability • protected by US Patent 6,140,887

· aqueous washable

Applications

satellite distribution

• GPS • cellular

• CATV

• low mainline loss, 1.3 dB typ. (5-1000 MHz)

Maximum Ratings


Operating Temperature	-40°C to 85°C
Storage Temperature	-55°C to 100°C
* Case temperature is defined as te	mperature on ground leads.
Permanent damage may occur if any	of these limits are exceeded.


Pin Connections

INPUT	3
OUTPUT	4
COUPLED	1
GROUND	2
75Ω TERM EXTERNAL	6
NOT USED	5

Outline Drawing

Lead #1 identifier shall be located in the cross-hatched area shown. Identifier may be either a molded or marked feature.-7






Outline Dimensions (inch)



Demo Board MCL P/N: TB-72 Suggested PCB Layout (PL-010)




NOTES: 1. TRACE WIDTH IS SHOWN FOR ROGERS R04350B WITH DIELECTRIC THICKNESS 0.030" ± 0.002"; COPPER: 1/2 0Z. EACH SIDE. FOR OTHER MATERIALS TRACE WIDTH MAY NEED TO BE MODIFIED. 2. BOTTOM SIDE OF THE PCB IS CONTINUOUS GROUND PLANE.

DENOTES PCB COPPER LAYOUT WITH SMOBC (SOLDER MASK OVER BARE COPPER)

🛛 DENOTES COPPER LAND PATTERN FREE OF SOLDER MASK Notes

Notes A. Performance and quality attributes and conditions not expressly stated in this specification document are intended to be excluded and do not form a part of this specification document. B. Electrical specifications and performance data contained in this specification document are based on Mini-Circuit's applicable established test performance criteria and measurement instructions. C. The parts covered by this specification document are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of the standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits website at www.minicircuits.com/MCLStore/terms.

2000



1000 FREQUENCY (MHz)

Electrical Schematic

COUPLING & DIRECTIVITY

DIRECTIVITY

1500

COUPLING

500

at RF level of -10 d

40

@30

DIRECT

0

0

COUPLING &) L≥20

TCD-9-1W-75+



CASE STYLE: DB714

+RoHS Compliant The +Suffix identifies RoHS Compliance. See our web site for RoHS Compliance methodologies and qualifications

	Available Tape and Reel at no extra cost
Reel Size	Devices/Reel
7"	20, 50, 100, 200, 500
13"	1000, 2000

Electrical Specifications


FREQ. RANGE (MHz)		PLING JB)	MAINLINE LOSS ¹ (dB)			DIRECTIVITY (dB)					VSWR (:1)	POV INPU	VER IT, W				
				L	n	N		U		L	N	Л	ι	J		L	MU
f _L -f _U	Nom.	Flatness	Тур.	Max.	Тур.	Max.	Тур.	Max.	Тур.	Min.	Тур.	Min.	Тур.	Min.	Тур.	Max.	Max.
5-1000	8.9±0.5	±0.6	1.3	2.1	1.3	2.0	1.8	2.4	21	17	15	_	10	_	1.30	0.5	1.0
1000-2000	8.5±0.5	±0.6	—	_	2.5	_	_	_	_	_	10	_	_	_	1.60	_	1.0

 $L = low range [f_{L} to 10 f_{L}]$ M = mid range [10 f_L to $f_U/2$] U= upper range [f_u/2 to f_u]

1. Mainline loss includes theoretical power loss at coupled port.

Typical Performance Data

Frequency (MHz)	Mainline Loss (dB)	Coupling (dB)	Directivity (dB)	Return Loss (dB)				
()	In-Out	In-Cpl	()	In	Out	Cpl		
5.00	1.29	8.99	21.24	16.92	25.24	16.42		
200.00	1.28	8.94	17.61	17.17	24.67	16.49		
600.00	1.46	8.84	11.06	12.00	15.49	12.84		
800.00	1.63	8.98	9.49	11.14	14.69	11.57		
1000.00	1.87	8.81	8.59	11.05	14.44	10.62		
1200.00	2.06	8.50	8.12	11.15	14.53	9.81		
1400.00	2.27	8.43	7.88	11.16	14.51	9.22		
1600.00	2.50	8.66	7.63	11.20	15.36	8.91		
1800.00	2.71	9.00	7.19	11.56	15.46	8.40		
2000.00	2.73	8.92	6.49	11.81	14.35	8.53		



REV. J M151107 ED-8571/1 TCD-9-1W-75 WZ/TD/CP/AM 151008