

High IP3

Low Noise Amplifier

ZHL-1010+

50Ω Medium High Power 50 to 1000 MHz

Features

- wideband, 50 to 1000 MHz
- low noise, 3.5 dB typ.
- high IP3, +46 dBm typ.
- very high IP2, 68-83 dBm typ.

Applications

- VHF/UHF
- cellular
- laboratory
- test equipment
- instrumentation



CASE STYLE: S32

Connectors Model
SMA ZHL-1010+

+RoHS Compliant

The +Suffix identifies RoHS Compliance. See our web site for RoHS Compliance methodologies and qualifications

Electrical Specifications

MODEL NO.	FREQ. (MHz)		GAIN (dB)		MAXIMUM POWER OUTPUT (dBm)		DYNAMIC RANGE		VSWR (:1) Max.		DC POWER	
	f_L	f_U	Min.	Flatness Max.	(1 dB Compr.) Min.	Input ¹ (no damage)	NF (dB) Typ.	IP3 (dBm) Typ.	In ²	Out	Volt (V) Nom.	Current (A) Max.
ZHL-1010+	50	1000	9.5	±0.6	+26	+22	3.5	+46	2.0	2.0	12	0.525

1. Open load is not recommended, potentially can cause damage. With no load derate max input power by 20 dB.
2. Input VSWR may degrade at 50-150 MHz up to 2.2:1.

Maximum Ratings


Operating Temperature -20°C to 65°C

Storage Temperature -55°C to 100°C


DC Voltage +13V Max.

Permanent damage may occur if any of these limits are exceeded.

Outline Drawing



MOUNTING INFORMATION FOR MODELS WITHOUT HEATSINK



Outline Dimensions (inch mm)

A	B	C	D	E	F	G	H	J	K	L	M	N	P	Q	R	S	T	wt
3.75	2.00	1.80	.19	3.375	.19	1.625	.144	.50	.40	.50	1.30	.10	.38	3.00	.30	2.60	.80	grams
95.25	50.80	45.72	4.83	85.73	4.83	41.28	3.66	12.70	10.16	12.70	33.02	2.54	9.65	76.20	7.62	66.04	20.32	220.0
wt. w/o heat sink																		150

Notes






- A. Performance and quality attributes and conditions not expressly stated in this specification document are intended to be excluded and do not form a part of this specification document.
B. Electrical specifications and performance data contained in this specification document are based on Mini-Circuit's applicable established test performance criteria and measurement instructions.
C. The parts covered by this specification document are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCLStore/terms.jsp



www.minicircuits.com P.O. Box 350166, Brooklyn, NY 11235-0003 (718) 934-4500 sales@minicircuits.com

REV. E
M162646
ZHL-1010+
EE-7064
171002
Page 1 of 2

FREQUENCY (MHz)	GAIN (dB)	DIRECTIVITY (dB)	VSWR (:1)		NOISE FIGURE (dB)	POUT at 1 dB COMPR. (dBm)
	12V	12V	IN	OUT	12V	12V
50.00	10.65	7.00	1.97	1.94	3.95	29.05
155.60	10.94	6.50	1.69	1.69	3.15	29.31
261.10	11.06	6.30	1.34	1.37	3.11	29.86
366.70	11.12	6.30	1.07	1.18	3.17	30.45
472.20	11.06	6.50	1.17	1.27	3.27	30.45
577.80	11.01	6.80	1.28	1.36	3.36	30.26
683.30	11.01	7.00	1.26	1.36	3.48	29.66
788.90	10.92	7.30	1.15	1.29	3.55	29.39
894.40	10.84	7.80	1.05	1.27	3.62	28.69
1000.00	10.72	8.20	1.08	1.35	3.80	27.90



Notes

A. Performance and quality attributes and conditions not expressly stated in this specification document are intended to be excluded and do not form a part of this specification document.

B. Electrical specifications and performance data contained in this specification document are based on Mini-Circuit's applicable established test performance criteria and measurement instructions.

C. The parts covered by this specification document are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCLStore/terms.jsp

