

Surface Mount Active Mixer

MA3-242LH+

Level -0 (LO Power -0 dBm) 850 to 1200 MHz


Maximum Ratings

Operating Temperature	-40°C to 85°C
Storage Temperature	-55°C to 100°C
RF Power	+13dBm
DC Current	40mA
LO Power	10dBm

Pin Connections

LO	11
RF	5
IF	5
DC	1
GROUND	4,6,7,8,9,10,12


Outline Drawing



Outline Dimensions (inch mm)

A	B	C	D	E	F	G	H	J
.118	.118	.035	.008	.057	.057	.009	---	.016
3.00	3.00	0.89	0.20	1.45	1.45	0.23	---	0.41
K	L	M	N	P	Q	R	wt	
.020	.127	.127	.049	.010	.020	.049	grams	
0.51	3.23	3.23	1.24	0.25	0.51	1.24	0.02	

Demo Board MCL P/N: TB-963+ Suggested PCB Layout (PL-531)



Features

- low conversion loss, 5.5 dB typ.
- wide bandwidth, 850 to 1200 MHz
- single ended mixer with LO amplifier
- aqueous washable
- low profile
- low cost
- E-PHEMT

Applications

- PCN
- defense & weather radar
- cellular
- UHF TV


Electrical Specifications at 25°C

Parameter	Min.	Typ.	Max.	Unit
Frequency Range, RF	850	985	1120	MHz
Frequency Range, LO	900	1050	1200	MHz
Frequency Range, IF	50	—	80	MHz
Conversion Loss	—	5.5	—	dB
RF to IF Isolation	—	20	—	dB
LO to IF Isolation	—	25	—	dB
IP3	—	18	—	dBm
RF Input at 1 dB Compression	—	14	—	dBm
Recommended Device Operation Current	—	22	—	mA
DC Voltage (Vs)	—	5.0	—	V
Device Voltage Variation vs. Temperature at 22 mA	—	-2.3	—	mV/°C
Device Voltage Variation vs. Current at 25°C	—	15.1	—	mV/mA

Typical Performance Data

Frequency		Conversion Loss (dB)	Isolation R-I (dB)	Isolation L-I (dB)	VSWR RF Port (:1)	VSWR LO Port (:1)	IP3 (dBm)
RF MHz	LO MHz	LO 0dBm	LO 0dBm	LO 0dBm	LO 0dBm	LO 0dBm	LO 0dBm
850.10	900.10	5.44	10.06	21.19	1.63	1.87	18.71
859.10	910.10	5.63	10.68	21.80	1.61	1.83	18.39
868.10	920.10	5.44	10.94	22.36	1.57	1.79	18.00
877.10	930.10	5.49	11.39	23.03	1.55	1.73	17.80
886.10	940.10	5.50	11.89	23.81	1.47	1.68	17.63
904.10	960.10	5.46	12.92	25.71	1.42	1.59	16.96
913.10	970.10	5.46	13.57	26.86	1.40	1.54	16.97
922.10	980.10	5.38	14.18	28.24	1.37	1.49	17.03
931.10	990.10	5.55	15.02	29.84	1.34	1.45	17.18
940.10	1000.10	5.57	15.71	31.89	1.34	1.41	17.23
1030.10	1100.10	5.63	29.56	25.81	1.47	1.33	17.90
1039.10	1110.10	5.54	28.76	24.47	1.49	1.33	18.02
1048.10	1120.10	5.52	27.96	23.35	1.51	1.33	18.24
1057.10	1130.10	5.53	27.35	22.18	1.51	1.34	18.60
1120.10	1200.10	5.67	17.11	17.15	1.38	1.54	20.10

Electrical Schematic



CASE STYLE: DQ1225

+RoHS Compliant

The +Suffix identifies RoHS Compliance. See our web site for RoHS Compliance methodologies and qualifications



Available Tape and Reel at no extra cost

Reel Size	Devices/Reel
7"	20, 50, 100, 200, 500, 1000, 2000








Notes

- Performance and quality attributes and conditions not expressly stated in this specification document are intended to be excluded and do not form a part of this specification document.
- Electrical specifications and performance data contained in this specification document are based on Mini-Circuit's applicable established test performance criteria and measurement instructions.
- The parts covered by this specification document are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCLStore/terms.jsp



www.minicircuits.com P.O. Box 350166, Brooklyn, NY 11235-0003 (718) 934-4500 sales@minicircuits.com

REV. OR
M162008
MA3-242LH+
JM/CP/AM
180115



Notes

- Performance and quality attributes and conditions not expressly stated in this specification document are intended to be excluded and do not form a part of this specification document.
- Electrical specifications and performance data contained in this specification document are based on Mini-Circuit's applicable established test performance criteria and measurement instructions.
- The parts covered by this specification document are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCLStore/terms.jsp

