

Coaxial

N-Type Fixed Attenuator

50Ω 1W 7dB DC to 6000 MHz


Maximum Ratings

Operating Temperature -45°C to 100°C

Storage Temperature -55°C to 100°C

Permanent damage may occur if any of these limits are exceeded.

Outline Drawing



Outline Dimensions (inch/mm)

B	D	E	wt
.68	2.11	.718	grams
17.27	53.59	18.24	72.5

Features

- wideband coverage, DC to 6000 MHz
- 1 watt rating
- rugged unibody construction
- off-the-shelf availability
- very low cost

Applications

- impedance matching
- signal level adjustment

UNAT-7+



CASE STYLE: FF779

Connectors Model
N-Type UNAT-7+

+RoHS Compliant

The +Suffix identifies RoHS Compliance. See our web site for RoHS Compliance methodologies and qualifications

Electrical Specifications



FREQ. RANGE (MHz)	ATTENUATION * (dB) Flatness **					VSWR (:1)					MAX. INPUT POWER (W)
	DC-3 GHz		3-4.5 GHz	4.5-6 GHz		DC-6 GHz	DC-3 GHz		3-4.5 GHz	4.5-6 GHz	
	Nom.	Typ.	Typ.	Typ.	Typ.	Typ.	Typ.	Max.	Typ.	Max.	
DC-6000	7±0.3	0.10	0.10	0.15	0.20	1.05	1.20	1.10	1.43	1.50	1.0

* Attenuation varies by 0.3 dB max. over temperature.

** Flatness= variation over band divided by 2.

Typical Performance Data

Frequency (MHz)	Attenuation (dB)	VSWR (:1)
10	6.97	1.00
50	6.96	1.00
100	7.00	1.01
500	7.06	1.03
1000	7.11	1.04
1600	7.10	1.04
2000	7.12	1.03
2500	7.11	1.04
3000	7.12	1.05
3500	7.14	1.09
4000	7.15	1.14
4500	7.16	1.21
5000	7.16	1.31
5500	7.18	1.45
6000	7.24	1.65



Notes

- A. Performance and quality attributes and conditions not expressly stated in this specification document are intended to be excluded and do not form a part of this specification document.
 B. Electrical specifications and performance data contained in this specification document are based on Mini-Circuit's applicable established test performance criteria and measurement instructions.
 C. The parts covered by this specification document are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCLStore/terms.jsp



www.minicircuits.com P.O. Box 350166, Brooklyn, NY 11235-0003 (718) 934-4500 sales@minicircuits.com

REV. E
M151107
ED-10269
UNAT-7+
UR/LC/CP
151012
Page 1 of 1