

Plug-In

Power Splitter/Combiner

6 Way-0° 50Ω 1 to 175 MHz

PSC-6-1+



CASE STYLE: C07

Maximum Ratings

Operating Temperature	-55°C to 100°C
Storage Temperature	-55°C to 100°C
Power Input (as a splitter)	1W max.
Internal Dissipation	0.5W max.
Permanent damage may occur if any of these limits are exceeded.	

Pin Connections

SUM PORT	1
PORT 1	3
PORT 2	4
PORT 3	8
PORT 4	12
PORT 5	16
PORT 6	15
GROUND	2,5,7,11,13,14
CASE GROUND	2,5,7,11,13,14
NOT USED	6,9,10

Features

- low insertion loss, 0.6 dB typ.
- high isolation, 30 dB typ.
- rugged welded case
- excellent amplitude unbalance, 0.1 dB typ.

Applications

- VHF
- radio communication
- instrumentation

+RoHS Compliant

The +Suffix identifies RoHS Compliance. See our web site for RoHS Compliance methodologies and qualifications

Electrical Specifications




FREQ. RANGE (MHz)	ISOLATION (dB)						INSERTION LOSS (dB) ABOVE 7.8 dB						PHASE UNBALANCE (Degrees)			AMPLITUDE UNBALANCE (dB)		
	L		M		U		L		M		U		L		M		U	
	Typ.	Min.	Typ.	Min.	Typ.	Min.	Typ.	Max.	Typ.	Max.	Typ.	Max.	Max.	Max.	Max.	Max.	Max.	Max.
f _L -f _U																		
1-175	35	25	30	23	25	18	0.6	1.2	0.6	1.1	0.6	1.3	2	4	8	0.1	0.3	0.6

L = low range [f_L to 10 f_L] M = mid range [10 f_L to f_U/2] U = upper range [f_U/2 to f_U]

Typical Performance Data

Frequency (MHz)	Total Loss¹ (dB)			Amplitude Unbalance (dB)	Isolation (dB)			Phase Unbal. (deg.)	VSWR S	VSWR 1	VSWR 3
	S-1	S-2	S-3		1-2	1-3	5-6				
1.00	8.32	8.31	8.33	0.03	33.73	33.10	33.56	0.16	1.23	1.29	1.30
3.00	8.20	8.19	8.22	0.03	31.72	31.45	31.60	0.14	1.24	1.20	1.21
9.00	8.16	8.16	8.19	0.04	31.13	31.02	31.05	0.14	1.26	1.16	1.16
20.00	8.21	8.20	8.24	0.04	31.01	30.97	30.95	0.19	1.26	1.15	1.15
35.00	8.27	8.27	8.30	0.04	30.82	30.90	30.70	0.28	1.27	1.14	1.14
50.00	8.30	8.29	8.33	0.04	30.50	30.69	30.31	0.38	1.28	1.14	1.14
65.00	8.30	8.29	8.33	0.04	30.08	30.42	29.79	0.51	1.28	1.14	1.14
80.00	8.34	8.33	8.37	0.04	29.59	30.08	29.24	0.60	1.29	1.13	1.14
95.00	8.41	8.38	8.43	0.05	29.12	29.73	28.72	0.75	1.29	1.13	1.13
110.00	8.45	8.42	8.46	0.04	28.70	29.42	28.25	0.83	1.29	1.11	1.12
120.00	8.44	8.41	8.45	0.05	28.42	29.20	27.96	0.92	1.29	1.11	1.11
130.00	8.44	8.41	8.45	0.05	28.19	29.03	27.72	0.97	1.29	1.11	1.11
145.00	8.49	8.45	8.49	0.06	27.86	28.79	27.42	1.11	1.28	1.12	1.12
165.00	8.60	8.54	8.59	0.08	27.44	28.48	27.03	1.21	1.27	1.11	1.12
175.00	8.63	8.57	8.61	0.09	27.21	28.30	26.86	1.43	1.27	1.11	1.12


PSC-6-1+ 1. Total Loss = Insertion Loss + 7.8dB splitter loss.



electrical schematic



Outline Drawing



Outline Dimensions (inch/mm)

A	B	C	D	E	F	G	H	wt
.770	.810	.380	.410	.030	.200	.20	.14	grams
19.56	20.57	9.65	10.41	0.76	5.08	5.08	3.56	11.0

Notes

- Performance and quality attributes and conditions not expressly stated in this specification document are intended to be excluded and do not form a part of this specification document.
- Electrical specifications and performance data contained in this specification document are based on Mini-Circuit's applicable established test performance criteria and measurement instructions.
- The parts covered by this specification document are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCLStore/terms.jsp



www.minicircuits.com P.O. Box 350166, Brooklyn, NY 11235-0003 (718) 934-4500 sales@minicircuits.com

REV. D
M151107
PSC-6-1+
HY/TD/CP/AM
151001