

IR, MIXER

5.8 to 6.1 GHz

IR6070MF2-108

PRODUCT FEATURE

- †Broadband Frequency Application
- †Excellent Conversion Loss
- †High Isolation
- †Frequency Converter Application

ABSOLUTE MAXIMUM RATING:

Operating Temperature:	-54°C to +125°C
Storage Temperature:	-65°C to +150°C
Peak Input Power for any Single Port:	+23 dBm Peak
Peak Input Power for all Port:	+26 dBm Peak
Peak Input Current @ 25°C:	100 mA

Parameters	SPECIFICATION @ 25°C				
	FREQ. (GHz)	MIN (dB)	TYPICAL (dB)	MAX (dB)	CONDITONS
CONVERSION LOSS					
RF OUTPUT	5.68				
LO INPUT	6.1				
IF INPUT	0.43 ± .04		7.0	7.5	
VSWR	LO & IF RF		2.0		
ISOLATION					
LO-RF		20	30		
LO-IF		20	28		
INPUT IP ₃		20 dB			
1 dB Compression Point			+12dBm		
LO Drive			+18 dBm		
IMAGE REJECTION		22 dB 22 dB	25 dB 25 dB		@IF=430 MHZ @IF=390-470 MHZ
OPERATING TEMP RANGE(°C)		-40		+85	

NOTES:

1. Typical values are measured at +25°C and are not guaranteed

IR, MIXER

5.8 to 6.1 GHz

IR6070MF2-108

