



TGA2622-SM

9 – 10 GHz 35 Watt GaN Power Amplifier


Product Description

Qorvo's TGA2622-SM is a packaged, high power X-Band amplifier fabricated on Qorvo's production 0.25um GaN on SiC process. Operating from 9-10GHz, the TGA2622-SM typically generates 35W of saturated output power with a power-added efficiency greater than 42% and 27.5dB of large signal gain.

The TGA2622-SM is packaged in a 7x7mm air-cavity, laminate based QFN. Both RF ports are internally DC blocked and matched to 50 ohms enabling simple system integration. Ideally suited for pulsed applications, the TGA2622-SM offers superior power, PAE and gain performance that can save costs on existing platforms while enabling the development of future systems.

Lead-free and RoHS compliant.

Evaluation boards are available upon request.




QFN 7x7 mm 22L

Product Features

- Frequency Range: 9 – 10 GHz
- P_{SAT} : 45.5 dBm @ $PIN = 18$ dBm
- PAE: 42% @ $PIN = 18$ dBm
- Power Gain: 27.5 dB @ $PIN = 18$ dBm
- Bias: $V_D = 28$ V, $I_{DQ} = 290$ mA, $V_G = -2.3$ V Typical
(Pulsed V_D : $PW = 100$ us and $DC = 10$ %)
- Package Dimensions: 7 x 7 x 1.75 mm

Performance is typical across frequency. Please reference electrical specification table and data plots for more details.

Functional Block Diagram



Applications

- Weather and Marine Radar

Ordering Information

Part	ECCN	Description
TGA2622-SM	3A001.b.2.b	9 – 10 GHz 35 W GaN Power Amplifier



TGA2622-SM

9 – 10 GHz 35 Watt GaN Power Amplifier

Electrical Specifications

Test conditions unless otherwise noted: 25 °C, $V_D = 28$ V, $I_{DQ} = 290$ mA, $V_G = -2.3$ V Typical,
Pulsed V_D : PW = 100 μ s, DC = 10%







Parameter		Min	Typ	Max	Units
Operational Frequency Range		9	–	10	GHz
Output Power @ $P_{IN} = 18$ dBm	Frequency = 9 GHz	45	45.7	–	dBm
	Frequency = 9.5 GHz	45	45.8	–	dBm
	Frequency = 10 GHz	45	45.8	–	dBm
Power Added Efficiency @ $P_{IN} = 18$ dBm	Frequency = 9 GHz	40	46.4	–	%
	Frequency = 9.5 GHz	40	46.4	–	
	Frequency = 10 GHz	35	43	–	
Small Signal Gain	Frequency = 9 GHz	–	31.5	–	dB
	Frequency = 9.5 GHz	–	32.7	–	
	Frequency = 10 GHz	–	31.4	–	
Input Return Loss	Frequency = 9 GHz	–	14.7	–	dB
	Frequency = 9.5 GHz	–	15	–	
	Frequency = 10 GHz	–	11	–	
Output Return Loss	Frequency = 9 GHz	–	10.6	–	dB
	Frequency = 9.5 GHz	–	9.3	–	
	Frequency = 10 GHz	–	12	–	
Output Power Temperature Coefficient From 25°C to 85°C ($P_{in} = 18$ dBm)		–	-0.02	–	dBm/°C

Recommended Operating Conditions







Parameter	Value
Drain Voltage	28 V
Drain Current (quiescent, I_{DQ})	290 mA
Gate Voltage	-2.3 V
Operating Temperature Range	-40 to 85 °C

Electrical specifications are measured at specified test conditions. Specifications are not guaranteed over all recommended operating conditions.







Performance Plots – Large Signal (Pulsed)









Performance Plots – Large Signal (Pulsed)









Performance Plots – Large Signal (Pulsed)









Performance Plots – Large Signal (Pulsed)








Performance Plots – Linearity (CW)







Performance Plots – Linearity (CW)



Performance Plots – Small Signal (CW)



Performance Plots – Small Signal (CW)



Thermal and Reliability Information




Parameter	Test Conditions	Value	Units
Thermal Resistance (θ_{JC}) ⁽¹⁾	$V_D = 28\text{ V}$, $I_{DQ} = 290\text{ mA}$, (Pulsed V_D : $PW = 100\text{ us}$, $DC = 10\%$), $T_{base} = 85\text{ }^\circ\text{C}$; $P_{DISS} = 8.12\text{ W}$	1.06	$^\circ\text{C/W}$
Channel Temperature (T_{CH}) (No RF drive)		94	$^\circ\text{C}$
Median Lifetime (T_M)		2.16×10^{12}	Hrs
Thermal Resistance (θ_{JC}) ⁽¹⁾	$V_D = 28\text{ V}$, $I_{DQ} = 290\text{ mA}$, (Pulsed V_D : $PW = 100\text{ us}$, $DC = 10\%$), $T_{base} = 85\text{ }^\circ\text{C}$, $V_D = 28\text{ V}$, $I_{D_Drive} = 3.1\text{ A}$, $P_{IN} = 20\text{ dBm}$, $P_{OUT} = 45.4\text{ dBm}$, $P_{DISS} = 52\text{ W}$	1.21	$^\circ\text{C/W}$
Channel Temperature (T_{CH}) (Under RF drive)		148	$^\circ\text{C}$
Median Lifetime (T_M)		2.19×10^9	Hrs

Notes:


1. Thermal Resistance measured to back of package.

Median Lifetime

Test Conditions: $V_D = +40\text{ V}$; Failure Criteria = 10 % reduction in I_{D_MAX} during DC Life Testing



Applications Circuit



Notes:

1. V_G : must be biased from both sides - $V_{G1,2}$ & V_{G3} can be tied together.
2. V_D : must be biased from both sides - $V_{D1,2}$ & V_{D3} can be tied together.


Bias Up Procedure

1. Set I_D limit to 3.5 A, I_G limit to 25 mA
2. Set V_G to -5.0 V (for pinch-off)
3. Set V_D +28 V; Ensure I_{DQ} is approx. 0 mA
4. Adjust V_G more positive until $I_{DQ} = 290$ mA ($V_G \sim -2.3$ V Typical)
5. Apply RF signal

Bias Down Procedure

1. Turn off RF supply
2. Reduce V_G to -5.0 V. Ensure $I_{DQ} \sim 0$ mA
3. Set V_D to 0 V
4. Turn off V_D supply
5. Turn off V_G supply


Pin Layout



Pin Description

Pin No.	Symbol	Description
1, 3, 12, 14	GND	Must be grounded on the PCB
2	RF _{IN}	Input; matched to 50 Ω; DC blocked
4, 22	V _{G1,2}	Gate Voltages 1,2; Bias network is required; must be biased from both sides; see recommended Application Information on page 12.
5, 21	V _{D1,2}	Drain voltages 1,2; Bias network is required; must be biased from both sides; see recommended Application Information on page 12.
6, 8, 9, 17, 18, 20	N/C	No internal connection
7, 19	V _{G3}	Gate Voltage 3; Bias network is required; must be biased from both sides; see recommended Application Information on page 12.
10, 11, 15, 16	V _{D3}	Drain voltage 3; Bias network is required; must be biased from both sides; see recommended Application Information on page 12.
13	RF _{OUT}	Output; matched to 50 Ω; DC blocked

Evaluation Board Layout




Notes: Both Top and Bottom VD and VG must be biased.

Bill of Materials

Reference Des.	Value	Description	Manuf.	Part Number
C1 – C8	1000 pF	Cap, 0402, 100 V, 10%, X7R	Various	
C9 – C10	10 μ F	Cap, 1206, 50 V, 20%, X5R	Various	
C11 – C14	0.01 μ F	Cap, 0402, 50 V, 10%, X7R	Various	
R1 – R6	10 ohms	Res, 0402, 50 V, 5%, SMD	Various	
R7 – R10	0 ohms	Res, 0402, jumpers required for the above EVB	Various	

Mechanical Information



Units: Millimeters (mm)

Tolerances: unless specified

x.xx = ± 0.25 ; x.xxx = ± 0.100

Materials:

Base: Laminate Substrate

Lid: Laminate

All metalized features are gold plated

Part is epoxy sealed

Marking:

TGA2622-SM: Part number

YY: Part Assembly year

WW: Part Assembly week


MXXX: Batch ID

Absolute Maximum Ratings


Parameter	Value
Drain Voltage (V_D)	40 V
Gate Voltage Range (V_G)	-8 to 0V
Drain Current (I_D)	4.3 A
Gate Current (I_G)	See I_{G_MAX} plot
Power Dissipation (P_{DISS}), 85 °C, CW	88 W
Input Power (P_{IN}), CW, 50 Ω , $V_D = 28V$, 85 °C	24 dBm
Input Power (P_{IN}), CW, VSWR 3:1, $V_D = 28V$, 85 °C	24 dBm
Channel Temperature (T_{CH})	275 °C
Mounting Temperature (30 seconds)	260 °C
Storage Temperature	-55 to 150 °C

Operation of this device outside the parameter ranges given above may cause permanent damage. These are stress ratings only, and functional operation of the device at these conditions is not implied.

Notes:



Recommended Soldering Temperature Profile



Handling Precautions

Parameter	Rating	Standard
ESD – Human Body Model (HBM)	Class 1B	ANSI/ESD/JEDEC JS-001
MSL – Moisture Sensitivity Level	Level 3	IPC/JEDEC J-STD-020



Caution!
ESD-Sensitive Device

Solderability

Compatible with the latest version of J-STD-020 Lead free solder, 260 °C.
Solder profiles available upon request.

RoHS Compliance

This product is compliant with the 2011/65/EU RoHS directive (Restrictions on the Use of Certain Hazardous Substances in Electrical and Electronic Equipment), as amended by Directive 2015/863/EU. This product also has the following attributes:

- Lead Free
- Antimony Free
- TBBP-A (C₁₅H₁₂Br₄O₂) Free
- PFOS Free
- SVHC Free
- Qorvo Green



Contact Information

For the latest specifications, additional product information, worldwide sales and distribution locations:

Tel: 1-844-890-8163

Web: www.qorvo.com

Email: info-sales@qorvo.com

For technical questions and application information: **Email:** info-products@qorvo.com

Important Notice

The information contained herein is believed to be reliable; however, Qorvo makes no warranties regarding the information contained herein and assumes no responsibility or liability whatsoever for the use of the information contained herein. All information contained herein is subject to change without notice. Customers should obtain and verify the latest relevant information before placing orders for Qorvo products. The information contained herein or any use of such information does not grant, explicitly or implicitly, to any party any patent rights, licenses, or any other intellectual property rights, whether with regard to such information itself or anything described by such information. **THIS INFORMATION DOES NOT CONSTITUTE A WARRANTY WITH RESPECT TO THE PRODUCTS DESCRIBED HEREIN, AND QORVO HEREBY DISCLAIMS ANY AND ALL WARRANTIES WITH RESPECT TO SUCH PRODUCTS WHETHER EXPRESS OR IMPLIED BY LAW, COURSE OF DEALING, COURSE OF PERFORMANCE, USAGE OF TRADE OR OTHERWISE, INCLUDING THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.**

Without limiting the generality of the foregoing, Qorvo products are not warranted or authorized for use as critical components in medical, life-saving, or life-sustaining applications, or other applications where a failure would reasonably be expected to cause severe personal injury or death.

Copyright 2016 © Qorvo, Inc. | Qorvo is a registered trademark of Qorvo, Inc.