

ESL1020A2 Pin-Schottky Diode Limiter

1.0-2.0 GHz Octave Band



Technical Characteristics

Product Features

Power Handling: 1 watt CW, 100W peak power
(1 usec Pulse Width, 0.1% Duty Cycle Derated to 20% @ +125 °C)
Internal DC return
Fast recovery time - 200 uSec typ.
Limiting threshold above +4dBm typ. & low typical output leakage
Low insertion loss

Maximum Ratings

Storage Temperature.....-65° to +125°C
Operating Temperature.....-55° to +90°C
Max Input Power.....+2 watts CW, 100 watts peak

Product Export Classification


ECCN: EAR 99 (unless otherwise specified)
HTS: 85543.70.8000

Specifications @ +25°C & -10 dBm input power.

Electrical Specifications

Parameters	Freq. (GHz)	Min.	Typical	Max.	Units
Insertion Loss	1.0 to 2.0		0.6		dB
VSWR	1.0 to 2.0		1.5:1		-
Leakage Power (CW)	1.0 to 2.0			+18	dBm CW
				+20	dBm Peak
Operating Temperature		-55		+90	° C

Outline drawing



Notes:

1. Limiter has an internal DC block.
2. Typical values are measured at +25°C and are not guaranteed.