


Applications


- Military Radar
- Commercial Radar



Product Features

- Frequency Range: 2.9 – 3.5 GHz
- Pout: > 48 dBm (at Pin = 24 dBm)
- Large Signal Gain: > 24 dB (at Pin = 24 dBm)
- PAE: > 54 % (at Pin = 24 dBm)
- Bias: $V_D = 28$ V, $I_{DQ} = 200$ mA, $V_G = -2.8$ V (Typ)
- Package Dimensions: 7.00 x 7.00 x 0.85 mm

Functional Block Diagram



General Description

TriQuint's TGA2817-SM is a high-power, S-band amplifier fabricated on TriQuint's TQGaN25 0.25um GaN on SiC production process. Covering 2.9-3.5 GHz, the TGA2817-SM provides > 48 dBm of saturated output power and > 24 dB of large-signal gain while achieving > 54 % power added efficiency.

The TGA2817-SM can also support a variety of operating conditions to best support system requirements. With good thermal properties, it can support a range of bias voltages and will perform well under pulse applications. The TGA2817-SM is matched to 50 ohms with integrated DC blocking caps on both I/O ports. It is ideal for use in both commercial and military radar systems.

Lead-free and RoHS compliant.

Evaluation board available on request.

Pad Configuration

Pad Number	Symbol
6, 7	RF Input
13, 48	V_{G1}
15, 46	V_{D1}
17, 44	V_{G2}
23, 38	V_{D2}
30, 31	RF Output
1-5, 8-12, 14, 16, 18-22, 24-29, 32-37, 39-43, 45, 47, 49	GND

Ordering Information

Part	ECCN	Description
TGA2817-SM	3A001.b.2.a	S-Band 60 W GaN Power Amplifier
TGA2817-SM_EVB	EAR99	TGA2817-SM Evaluation Board

Absolute Maximum Ratings

Parameter	Value
Drain Voltage (V_D)	40 V
Drain Current (I_{D1}/I_{D2})	1.4/5.8 A
Gate Current (I_G)	See graph
Dissipated Power (P_{DISS})	92 W
Input Power: 50 Ω , 85 °C ¹	30 dBm
Input Power: 3:1 VSWR, 85 °C ¹	28 dBm
Channel Temperature, T_{CH}	275 °C
Storage Temperature	-55 to 150 °C

¹ Based on die performance

Operation of this device outside the parameter ranges given above may cause permanent damage.

Recommended Operating Conditions

Parameter	Value
Drain Voltage	28 V
Drain Current (quiescent, I_{DQ})	200 mA
Drain Current (under drive, I_D)	4.6 A
Gate Voltage	-2.8 V
Operating Temperature	-40 to 85 °C

Electrical specifications are measured at specified test conditions. Specifications are not guaranteed over all recommended operating conditions.

Electrical Specifications

Test conditions, unless otherwise noted: 25 °C, $V_D = 28$ V, $I_{DQ} = 200$ mA, Pulse Width = 100 μ s, Duty Cycle = 10%

Parameter	Min	Typical	Max	Units
Frequency	2.9		3.5	GHz
Output Power ($P_{IN} = 24$ dBm)		> 48.0		dBm
Large Signal Gain ($P_{IN} = 24$ dBm)		> 24.2		dB
Power Added Efficiency ($P_{IN} = 24$ dBm)		> 54.0		%
Input Return Loss		> 8.3		dB
Output Power Temperature Coefficient		-0.006		dBm/°C




Specifications

Thermal and Reliability Information

Parameter	Conditions	Value	Units
Thermal Resistance (θ_{JC}) ⁽¹⁾	$T_{BASE} = 85^{\circ}\text{C}$, $V_D = 28\text{ V}$, $I_D = 200\text{ mA}$ (quiescent DC, small signal), $P_{DISS} = 6.4\text{ W}$	1.094	$^{\circ}\text{C/W}$
Channel Temperature (T_{CH})		92.0	$^{\circ}\text{C}$
Median Lifetime (T_M)		2.90E+12	Hrs
Thermal Resistance (θ_{JC}) ⁽¹⁾	$T_{BASE} = 85^{\circ}\text{C}$, $V_D = 28\text{ V}$, $I_D = 4.5\text{ A}$, $P_{IN} = 24\text{ dBm}$, $P_{OUT} = 48.5\text{ dBm}$, $PW = 100\text{ us}$, DC = 10%, $P_{DISS} = 53\text{ W}$	0.698	$^{\circ}\text{C/W}$
Channel Temperature (T_{CH})		122.0	$^{\circ}\text{C}$
Median Lifetime (T_M)		4.79E+10	Hrs
Thermal Resistance (θ_{JC}) ⁽¹⁾	$T_{BASE} = 85^{\circ}\text{C}$, $V_D = 32\text{ V}$, $I_D = 5.1\text{ A}$, $P_{IN} = 24\text{ dBm}$, $P_{OUT} = 49.4\text{ dBm}$, $PW = 100\text{ us}$, DC = 10%, $P_{DISS} = 74\text{ W}$	0.716	$^{\circ}\text{C/W}$
Channel Temperature (T_{CH})		138.0	$^{\circ}\text{C}$
Median Lifetime (T_M)		6.85E+09	Hrs







Median Lifetime

Test Conditions: 40 V
Failure Criterion = 10% reduction in $I_{D\text{ MAX}}$






Typical Performance

Test conditions unless otherwise noted: Temp. = 25 °C









Typical Performance

Test conditions unless otherwise noted: Temp. = 25 °C








Typical Performance

Test conditions unless otherwise noted: Temp. = 25 °C, Pulsed input power PW = 100 us, Duty Cycle = 10%








Typical Performance

Test conditions unless otherwise noted: Pulsed input power PW = 100 us, Duty Cycle = 10%




Typical Performance

Test conditions unless otherwise noted: Pulsed input power PW = 100 us, Duty Cycle = 10%



Application Circuit



Notes:

1. V_G and V_D must be biased from both sides (top and bottom).


Bias-up Procedure

1. Set I_D limit to 6000mA, I_G limit to 40mA
2. Set V_G to -6.0 V
3. Set V_D +28 V
4. Adjust V_G more positive until $I_{DQ} = 200mA$ ($V_G \sim -2.8$ V Typical)
5. Apply RF signal

Bias-down Procedure

1. Turn off RF signal
2. Reduce V_G to -6.0V. Ensure $I_{DQ} \sim 0mA$
3. Set V_D to 0V
4. Turn off V_D supply
5. Turn off V_G supply


Evaluation Board and Mounting Detail



RF Layer is 0.008" thick Rogers Corp. RO40003C ($\epsilon_r = 3.35$). Metal layers are 0.5 oz. copper. The microstrip line at the connector interface is optimized for the Southwest Microwave end launch connector 1092-02A-5.

Reference Des.	Component	Value	Manuf.	Part Number
C1, C2	Surface Mount Cap	10 uF, 20 %, 50 V (1206), X5R	Various	
C3 – C10	Surface Mount Cap	1000 pF, 10 %, 50 V (0402), X7R	Various	
C11 – C14	Surface Mount Cap	1.0 uF, 10 %, 25 V (0402), X7R	Various	
R1, R2	Surface Mount Res	0 Ohm, 5 % (0603)	Various	

Mechanical Drawing and Pad Description



Dimensions are in mm.

Pad No.	Symbol	Description
1-5, 8-12, 14, 16, 18-22, 24-29, 32-37, 39-43, 45, 47, 49	GND	Ground connection.
6, 7	RF Input	50 Ohm RF input. Pad is capacitively coupled to block on-chip DC voltages.
13, 48	V _{G1}	1 st Stage Gate Voltage; bias network is required; must be biased from both sides (V _{G1} and V _{G2} can be tied together in application)
15, 46	V _{D1}	1 st Stage Drain Voltage; bias network is required; must be biased from both sides (V _{D1} and V _{D2} can be tied together in application)
17, 44	V _{G2}	2 nd Stage Gate Voltage; bias network is required; must be biased from both sides (V _{G1} and V _{G2} can be tied together in application)
23, 38	V _{D2}	2 nd Stage Drain Voltage; bias network is required; must be biased from both sides (V _{D1} and V _{D2} can be tied together in application)
30, 31	RF Output	50 Ohm RF output. Pad is capacitively coupled to block on-chip DC voltages. Pad is DC grounded.

Product Compliance Information

ESD Sensitivity Ratings



Caution! ESD-Sensitive Device

ESD Rating: Class 1B
Value: 500 V
Test: Human Body Model (HBM)
Standard: JEDEC Standard JS-001-2014

ESD Rating: Class C3
Value: 1000 V
Test: Charged Device Model (CDM)
Standard: JEDEC Standard JS-002-2014

MSL Rating

MSL Rating: Level 3
Test: 260 °C convection reflow
Standard: JEDEC Standard IPC/JEDEC J-STD-020

ECCN

US Department of Commerce: 3A001.b.2.a

Solderability

Compatible with the latest version of J-STD-020 Lead free solder, 260 °C.


RoHS-Compliance

This part is compliant with EU 2002/95/EC RoHS directive (Restrictions on the Use of Certain Hazardous Substances in Electrical and Electronic Equipment).

This product also has the following attributes:

- Lead Free
- Halogen Free (Chlorine, Bromine)
- Antimony Free
- TBBP-A (C15H12Br4O2) Free
- PFOS Free
- SVHC Free

Recommended Soldering Temperature Profile



Contact Information

For the latest specifications, additional product information, worldwide sales and distribution locations, and information about TriQuint:

Web: www.triquint.com
Email: info-sales@tqs.com

Tel: +1.972.994.8465
Fax: +1.972.994.8504

For technical questions and application information: **Email:** info-products@tqs.com

Important Notice

The information contained herein is believed to be reliable. TriQuint makes no warranties regarding the information contained herein. TriQuint assumes no responsibility or liability whatsoever for any of the information contained herein. TriQuint assumes no responsibility or liability whatsoever for the use of the information contained herein. The information contained herein is provided "AS IS, WHERE IS" and with all faults, and the entire risk associated with such information is entirely with the user. All information contained herein is subject to change without notice. Customers should obtain and verify the latest relevant information before placing orders for TriQuint products. The information contained herein or any use of such information does not grant, explicitly or implicitly, to any party any patent rights, licenses, or any other intellectual property rights, whether with regard to such information itself or anything described by such information.

TriQuint products are not warranted or authorized for use as critical components in medical, life-saving, or life-sustaining applications, or other applications where a failure would reasonably be expected to cause severe personal injury or death.