



RF-LAMBDA

LEADER OF RF BROADBAND SOLUTIONS

RFDAT0622G5A

Absorptive Digital Control Attenuator 6 – 22GHz



Features

- Wide Band Operation 6-22GHz
- 0.75dB LSB Steps to 23.25dB
- Single Positive Control Line Per Bit

Typical Applications

- Wireless Infrastructure
- Test and Measurement
- Fibre Optics

Electrical Specifications, TA = +25° C, Vdd = +5V & VCTL = 0/ +5V

Description	PN:RFDAT0622G5A						
	Absorptive Digital Attenuator						
Parameters	Min	Typ	Max	Min	Typ	Max	Units
Frequency Range	6-8			8-22			GHz
Attenuation Range			23.25			23.25	dB
Attenuation Flatness: (Referenced to Insertion Loss)		±3			±1.5		dB
Control Bits			5			5	Bit
Control Step size	0.75			0.75			dB
Insertion Loss		13	15		7.2	8	dB
Insertion Loss Temperature Coefficient		0.003			0.003		dB/°C
Input VSWR(All Atten. States)		3.5	4.5		2.0	2.5	: 1
Output VSWR (All Atten. States)		3.5	4.5		2.0	2.5	: 1
Input 0.1 dB Compression Point (Po.1dB)			35			35	dBm
IIP3		36			36		dBm
Switching Speed		100			100		ns
Weight	0.71						ounces
Impedance	50						Ω
Bias Current (+5V)	40						mA
Input / Output Connectors	SMA-Female						
Interface and Control Connector	MICRO-D9 (Female)						
Finish	Gold Plated						
Material	Aluminum						
Seal	Hermetically Sealed (Optional)						

Absorptive Digital Control Attenuator 6 – 22 GHz



RF-LAMBDA

LEADER OF RF BROADBAND SOLUTIONS

RFDAT0622G5A

Absolute Maximum Ratings

Biasing	+5V±10%
TTL Control Voltage	0~0.8V / 2.8~5V

Ordering Information

Part No.	ECCN	Description
RFDAT0622G5A	EAR99	6-22GHz Digital Control Attenuator

Environmental Specifications and Test Standards

Parameter	Standard	Description
Operational Temperature	MIL-STD-39016	-45°C~+85°C
Storage Temperature		-55°C~+125°C
Thermal Shock		1 Hour@ -45°C → 1 Hour @ +85°C (5 Cycles)
Random Vibration		Acceleration Spectral Density 6 (m/s) Total 92.6 RMS
Electrical & Temperature Burn In		Temperature +85°C for 72 Hours
Shock		1. Weight >20g, 50g half sine wave for 11ms, Speed variation 3.44m/s 2. Weight <=20g, 100g Half sine wave for 6ms, Speed variation 3.75m/s 3. Total 18 times (6 directions, 3 repetitions per direction).
Altitude		Standard: 30,000 Ft (Epoxy Sealed Controlled Environment) Optional: Hermetically Sealed (60,000 ft. 1.0 PSI min)
Hermetically Sealed (Optional)	MIL-STD-883	MIL-STD-883 (For Hermetically Sealed Units)

Absorptive Digital Control Attenuator 6 – 22 GHz




RF-LAMBDA

LEADER OF RF BROADBAND SOLUTIONS


RFDAT0622G5A

Typical Performance Plots


Insertion Loss @+25°C




Input VSWR @+25°C




Output VSWR @+25°C




Insertion Loss @-45°C




Input VSWR @-45°C




Output VSWR @-45°C



Insertion Loss @+85°C



Input VSWR @+85°C



Absorptive Digital Control Attenuator 6 – 22 GHz




RF-LAMBDA


LEADER OF RF BROADBAND SOLUTIONS

RFDAT0622G5A


Output VSWR @+85°C




Attenuation vs. Frequency




VSWR vs. Attenuation(S11)




VSWR vs. Attenuation(S22)




Attenuation Range Linearity




Attenuation Step Error Per Bit (dB)



Accumulated Attenuation Error(dB)



Relative Phase Shift



Absorptive Digital Control Attenuator 6 – 22 GHz





RF-LAMBDA

LEADER OF RF BROADBAND SOLUTIONS

RFDAT0622G5A

Outline Drawing:

All Dimensions in mm [inches]



1 2 3 4 5 6 7 8 9
+5V NC GND C1 C2 C3 C4 C5 NC
MICRO-D9(Female)

Truth Table

Control Voltage Input					Attenuation State
C5	C4	C3	C2	C1	
0	0	0	0	0	Reference IL
0	0	0	0	1	0.75dB
0	0	0	1	0	1.5dB
0	0	1	0	0	3dB
0	1	0	0	0	6dB
1	0	0	0	0	12dB
1	1	1	1	1	23.25dB



Important Notice

The information contained herein is believed to be reliable. RF-Lambda makes no warranties regarding the information contained herein. RF-Lambda assumes no responsibility or liability whatsoever for any of the information contained herein. RF-Lambda assumes no responsibility or liability whatsoever for the use of the information contained herein. The information contained herein is provided "AS IS, WHERE IS" and with all faults, and the entire risk associated with such information is entirely with the user. All information contained herein is subject to change without notice. Customers should obtain and verify the latest relevant information before placing orders for RF-Lambda products. The information contained herein or any use of such information does not grant, explicitly or implicitly, to any party any patent rights, licenses, or any other intellectual property rights, whether with regard to such information itself or anything described by such information. RF-Lambda products are not warranted or authorized for use as critical components in medical, life-saving, or life sustaining applications, or other applications where a failure would reasonably be expected to cause severe personal injury or death.