

ULTRA WIDE BAND 100-200MHz ISOLATOR RFLI101M10M20


2.0	Environment specifications	
2.1	Opt. Temp.	-20°C~+70°C
2.2	Storage Temp.	-40°C~+85°C
2.3	Altitude	45000 ft
2.4	Vibration	10g rms (15 degree 2KHz)
2.5	Humidity	100% RH at 35c, 95%RH at 40 deg c
2.6	Shock	20G for 11msc





1.0	Mechanical Specifications	
1.1	Coaxial	SMA-F or N-F
1.2	External Finish	Nickle Plated
1.3	Rotation	Clockwise / Counter-clockwise











PN	Frequency (MHz)	Insertion loss (dB)	Isolation (dB) min	VSWR (max)	Forward Power (CW)	Reverse Power (CW)
RFLI101M10M20	100-200	1.2	16	1.5	20	5

* All spec. above in 25C degree only.

PAGE 1 OF 1

DATE JAN 8th 2003

PROPRIETARY INFORMATION
THE INFORMATION CONTAINED IN THIS DOCUMENT IS THE PROPERTY OF RF-LAMBDA EXCEPT AS SPECIFICALLY AUTHORIZED IN WRUTUBG BT RF-LAMBDA. THE HOLDER OF THIS DOUCUMENT SHALL KEEP ALL INFORMATION CONTAINED HEREIN CONFIDENTIAL AND SHALL PROTECT SAME IN THE WHOLE OR IN PART FROM DISCLOSURE AND DISSEMINATION OF ALL THIRD PARTIES AND SHALL USE SAME FOR OPERATING AND MAINTENANCE PURPOSES ONLY

DESIGN RFPC

RF-LAMBDA RFPC

CAD MODEL REVISION 02-1

ASSEMBLY REVISION VS23

ASSEMBLY NAME RFLVR54

DRAWING NUMBER D02-12

RFLI101M10M20
ULTRA WIDE BAND
ISOLATOR

www.rflambda.com

RF-LAMBDA

SIZE LT

SHEETS 1 OF 1