



Port Configuration

Output-1	Port-1
Input	Port-2
Output-2	Port-3
Ground	Half plated holes 4 corners



All half thru plated holes on all sides need to be grounded to main board

Electrical Specifications:

Frequency Range:	5 – 3000	Mhz	
Insertion Loss:	2.6	dB	Max
Amplitude Balance:	0.5	dB	Max
Isolation:	15	dB	Max
Phase Balance:	6.0	degree	Max
VSWR Input:	1.60:1		Max
VSWR Output:	1.60:1		Max
Power Input:	1	Watt	Max
Operating Temperature:	-40 °C to +85 °C		
Storage Temperature:	-55 °C to +100 °C		
Theoretical loss for 2-way divider is 3.0 dB			
Input power is specified for load VSWR better than 1.20:1.			

SigaTek

423 Black Oak Ridge Rd.
Wayne, NJ 07470
Ph: 973-706-8475, Fax: 973-832-4435
www.sigatek.com

SP15K2

Power Divider 2-way Surface Mount

Dimensions are in inches and (mm)
Decimal Tolerance:
2 place +- 0.020
3 place +- 0.010

CAGE CODE : 69UC1

Notes: All dimensions are typical unless they are specified.
Specifications are subject to change at any time without any notice.
Copy or distribution of this drawing is not allowed without Sigatek's approval.