




### Port Configuration

|          |                             |
|----------|-----------------------------|
| Output-1 | Port-1                      |
| Input    | Port-2                      |
| Output-2 | Port-3                      |
| Output-3 | Port-4                      |
| Ground   | Half plated holes 4 corners |



### Electrical Specifications:

|                                                            |                   |        |     |
|------------------------------------------------------------|-------------------|--------|-----|
| Frequency Range:                                           | 5 – 1500          | Mhz    |     |
| Insertion Loss:                                            | 1.6               | dB     | Max |
| Amplitude Balance:                                         | 0.5               | dB     | Max |
| Isolation:                                                 | 20                | dB     | Max |
| Phase Balance:                                             | 7                 | degree | Max |
| VSWR Input:                                                | 1.70:1            |        | Max |
| VSWR Output:                                               | 1.70:1            |        | Max |
| Power Input:                                               | 1                 | Watt   | Max |
| Operating Temperature:                                     | -40 °C to +85 °C  |        |     |
| Storage Temperature:                                       | -55 °C to +100 °C |        |     |
| Theoretical loss for 2-way divider is 3.0 dB               |                   |        |     |
| Input power is specified for load VSWR better than 1.20:1. |                   |        |     |

**SigaTek**

423 Black Oak Ridge Rd.  
Wayne, NJ 07470  
Ph: 973-706-8475, Fax: 973-832-4435  
www.sigatek.com

**SP12K3**

**Power Divider 3-way  
Surface Mount**

Dimensions are in inches and (mm)  
Decimal Tolerance:  
2 place +/- 0.020  
3 place +/- 0.010

**CAGE CODE : 69UC1**

Notes: All dimensions are typical unless they are specified.  
Specifications are subject to change at any time without any notice.  
Copy or distribution of this drawing is not allowed without Sigatek's approval.