

80W Coaxial Fixed Attenuator DC - 12.4GHz





Features

Low VSWR

Typical Applications

- Microwave Signal Attenuation.
- Test and Measurement.
- Research and Development.
- Radar Applications

Electrical Specifications, 25°C

Part Number	Frequency Range (GHz)	Attenuation (dB)	Attenuation Accuracy (dB)	VSWR	Power (CW)	Peak Power(KW)
RFS80G12B	DC-12.4GHz	3	+0.9/-0.5	1.3	80	1
		10	-0.5/+2.0	1.35		
		20	-0.5/+1.0	1.35		
		30	-1.0/+2.0	1.35		
		40	-1.0/+2.0	1.35		

Mechanical Specifications


Weight	9.52 Ounces	
Coaxial Connector	N ,7/16	
External Body Finish	Body painted with gray/black epoxy enamel	

Environmental Specifications


Operational Temperature (°C)	-40~ +85	
Storage Temperature (°C)	-55 ~ +125	
Altitude	42000 ft	
Vibration	10g RMS (15 degrees 2KHz)	
Humidity	100% RH at 35c, 95%RH at 40 ℃	
Shock	20G for 11msec	
Cooling	FAN required for long time operation	








S12



Outline Drawing:

All Dimensions in mm [inches]



Important Notice

The information contained herein is believed to be reliable. RF-Lambda makes no warranties regarding the information contained herein. RF-Lambda assumes no responsibility or liability whatsoever for any of the information contained herein. RF-Lambda assumes no responsibility or liability whatsoever for the use of the information contained herein. The information contained herein is provided "AS IS, WHERE IS" and with all faults, and the entire risk associated with such information is entirely with the user. All information contained herein is subject to change without notice. Customers should obtain and verify the latest relevant information before placing orders for RF-Lambda products. The information contained herein or any use of such information does not grant, explicitly or implicitly, to any party any patent rights, licenses, or any other intellectual property rights, whether with regard to such information itself or anything described by such information.

RF-Lambda products are not warranted or authorized for use as critical components in medical, life-saving, or life sustaining applications, or other applications where a failure would reasonably be expected to cause severe personal injury or death.