







WAVEGUIDE WR42 50W ATTENUATOR

— RFWAT42W050



1.0	Mechanical Specifications	
1.1	Waveguide type	Rectangular Waveguide WR42
1.2	Flange type	CPRG, CPRF, COVER, CHOKE available
1.3	Flange Holes	Through
1.4	Basis-material	Alloyed Cuprum 0.1kg
1.5	Internal Body Finish	Silver Plated chromate or conversion
1.6	External Body Finish	Body painted with gray/black epoxy enamel

2.0	Environment specifications	
2.1	Operation Temp.	-40°C~+85°C
2.2	Storage Temp.	-60°C~+125°C
2.3	Altitude	45000 ft
2.4	Vibration	10g rms (15 degree 2KHz)
2.5	Humidity	100% RH at 35c, 95%RH at 40 deg c
2.6	Shock	20G for 11msc

3.0	Electrical Specifications	
3.1	Frequency Range	17.6-26.7GHz
3.2	Forward Power	50W (CW)
3.3	Peak Power	1KW (8us pulse)
3.4	Attenuation	3dB~50dB
3.5	VSWR	1.20:1 (type.)

PAGE 1 OF 1		DATE Sep 20th 2005
THE INFORMATION CONTAINED IN THIS DOCUMENT IS THE PROPERTY OF RF-LAMBDA. THE HOLDER OF THIS DOCUMENT SHALL KEEP ALL INFORMATION CONTAINED HEREIN CONFIDENTIAL AND SHALL PROTECT SAME IN THE WHOLE OR IN PART FROM DISCLOSURE AND DISSEMINATION OF ALL THIRD PARTIES AND SHALL USE SAME FOR OPERATING AND MAINTENANCE PURPOSES ONLY		DESIGN
		RFPC
		RF-LAMBDA
		RFPC
 RFWAT42W050 WAVEGUIDE ATTENUATOR		CAD MODEL REVISION
		11
		ASSEMBLY REVISION
		VSSDS
www.rflambda.com		ASSEMBLY NAME
		RFLVR05
RF-LAMBDA		DRAWING NUMBER
		D05-1
SIZE LT	SHEETS	1 OF 1