




RF-LAMBDA

LEADER OF RF BROADBAND SOLUTIONS

RFWAT28W025

25W WR28 Waveguide Attenuator 26.5 – 40GHz



Note: The photo is for illustration purposes only.
Please refer to the outline drawing.



Features

- Waveguide Attenuator.
- 20dB, 30dB
- 25W Power Handling.

Typical Applications

- Radar Applications.
- Military and Defense.

Electrical Specifications , $T_A=25\text{ }^{\circ}\text{C}$

Parameters		Min.	Typ.	Max.	Units
Frequency Range		26.5		40	GHz
VSWR			1.20		: 1
Attenuation		20dB, 30dB			
Power Handling				25	W
Peak Power (8us pulse)				1	KW
Waveguide Type		WR28			
Flange type		CPRG, CPRF, COVER, CHOKE available			
Flange Holes		Through			
Basis-material		Alloyed Cuprum 0.1kg			
Finish	Internal Body	Silver Plated chromate or conversion			
	External Body	Body painted with gray/black epoxy enamel			

25W WR28 Waveguide Attenuator 26.5 – 40GHz




RF-LAMBDA

LEADER OF RF BROADBAND SOLUTIONS

RFWAT28W025

Environmental Specifications and Test Standards

Parameter	Standard	Description
Operational Temperature	MIL-STD-39016	-40°C~+85°C
Storage Temperature		-60°C~+125°C
Thermal Shock		1 Hour@ -45°C → 1 Hour @ +85°C (5 Cycles)
Random Vibration		Acceleration Spectral Density 6 (m/s) Total 92.6 RMS
Electrical & Temperature Burn In		Temperature +85°C for 72 Hours
Shock		1. Weight >20g, 50g half sine wave for 11ms, Speed variation 3.44m/s 2. Weight <=20g, 100g Half sine wave for 6ms, Speed variation 3.75m/s 3. Total 18 times (6 directions, 3 repetitions per direction).
Altitude	MIL-STD-883	Standard: 30,000 Ft (Epoxy Sealed Controlled Environment) Optional: Hermetically Sealed (60,000 ft. 1.0 PSI min)
Hermetically Sealed (Optional)		MIL-STD-883 (For Hermetically Sealed Units)



25W WR28 Waveguide Attenuator 26.5 – 40GHz




RF-LAMBDA

LEADER OF RF BROADBAND SOLUTIONS

RFWAT28W025

Outline Drawing:

All Dimensions in mm



25W WR28 Waveguide Attenuator 26.5 – 40GHz

Important Notice

The information contained herein is believed to be reliable. RF-Lambda makes no warranties regarding the information contained herein. RF-Lambda assumes no responsibility or liability whatsoever for any of the information contained herein. The information contained herein is provided "AS IS, WHERE IS" and with all faults, and the entire risk associated with such information is entirely with the user. All information contained herein is subject to change without notice. Customers should obtain and verify the latest relevant information before placing orders for RF-Lambda products. The information contained herein or any use of such information does not grant, explicitly or implicitly, to any party any patent rights, licenses, or any other intellectual property rights, whether with regard to such information itself or anything described by such information.

RF-Lambda products are not warranted or authorized for use as critical components in medical, life-saving, or life sustaining applications, or other applications where a failure would reasonably be expected to cause severe personal injury or death.