

SPECIFICATION SHEET

JFW MODEL 50T-274

TERMINATION

JFW Industries, Inc.
Phone: 317-887-1340
sales@jfwindustries.com
www.jfwindustries.com

Frequency Range DC-40 GHz

Available Model Numbers 50T-274 2.9MM M (2.9mm male)
50T-274-BC 2.9MM M (2.9mm male with bead chain)
50T-274 2.9MM F (2.9mm female)
50T-274-HEX 2.9MM F (2.9mm female with 5/16 hex)

Impedance 50 Ohms nominal


VSWR 1.2:1 maximum

RF Input Power 1 Watt average @ +25°C
(derate linearly to 0 Watts @ +125°C)

RF Connector 2.9 mm male or female
(mates mechanically with SMA, 3.5 mm, and K connectors)

Operating Temperature Range -55°C to +125°C

Outline Drawing Numbers 092-8073 (50T-274 2.9MM M)
092-8073-01 (50T-274-BC 2.9MM M)
092-9128 (50T-274 2.9MM F)
092-9128-01 (50T-274-HEX 2.9MM F)



ECR/ECN #	DATE	REV	APPR / DATE	ECR/ECN #	DATE	REV	APPR / DATE
9999	02/21/2003	A	SL 06/11/2003	28878	07/21/2018	D	TRS 07/16/2018
10241	12/06/2004	B	SL 12/06/2004	28951	08/14/2018	E	TRS 08/14/2018
24460	08/22/2014	C	TRS 08/22/2014	29048	09/27/2018	F	TRS 09/27/2018