

# 150W High Power Embedded Termination DC – 8GHz



Note: The photo is for illustration purposes only. Please refer to the outline drawing.



#### **Features**

- High Power Handling: 150W
- Low VSWR

## **Typical Applications**

- Research and Development
- Wireless Infrastructure
- Test and Measurement
- Microwave Subsystems

# Electrical Specifications, $T_A=25$ °C

Parameters	Min.	Тур.	Max.	Units
Frequency Range	DC		8	GHz
VSWR			1.25	:1
Average Power			150	w
Peak Power			10	KW
Nominal Impedance	50 Ω		Ω	
Weight	6.70 Ounces			
Coaxial Connector	N,SMA			
Material	Aluminum			


## **Environmental Specifications and Test Standards**

Parameter	Standard	Description	
Operational Temperature		-45℃~+85℃	
Storage Temperature		-55°C~+125°C	
Thermal Shock		1 Hour@ -45°C → 1 Hour @ +85°C (5 Cycles)	
Random Vibration		Acceleration Spectral Density 6 (m/s) Total 92.6 RMS	
Electrical & Temperature Burn In	MIL-STD-39016	Temperature +85°C for 72 Hours	
Shock		1. Weight >20g, 50g half sine wave for 11ms, Speed variation 3.44m/s 2. Weight <=20g, 100g Half sine wave for 6ms, Speed variation 3.75m/s 3. Total 18 times (6 directions, 3 repetitions per direction).	
Altitude		Standard: 30,000 Ft (Epoxy Sealed Controlled Environment) Optional: Hermetically Sealed (60,000 ft. 1.0 PSI min)	
Hermetically Sealed (Optional)	MIL-STD-883	MIL-STD-883 (For Hermetically Sealed Units)	



# **Outline Drawing:**

All Dimensions in mm [inches]



#### **Important Notice**

The information contained herein is believed to be reliable. RF-Lambda makes no warranties regarding the information contained herein. RF-Lambda assumes no responsibility or liability whatsoever for any of the information contained herein. RF-Lambda assumes no responsibility or liability whatsoever for the use of the information contained herein. The information contained herein is provided "AS IS, WHERE IS" and with all faults, and the entire risk associated with such information is entirely with the user. All information contained herein is subject to change without notice. Customers should obtain and verify the latest relevant information before placing orders for RF-Lambda products. The information contained herein or any use of such information does not grant, explicitly or implicitly, to any party any patent rights, licenses, or any other intellectual property rights, whether with regard to such information itself or anything described by such information.

RF-Lambda products are not warranted or authorized for use as critical components in medical, life-saving, or life sustaining applications, or other applications where a failure would reasonably be expected to cause severe personal injury or death.