



SMA DC-18GHz 1.0W TERMINATION

--- RFST1G18sM




2.0	Environment specifications	
2.1	Operation Temp.	-50°C~+120°C (case temp.)
2.2	Storage Temp.	-20°C~+70°C
2.3	Vibration	10g rms (15 degree 2KHz)
2.4	Humidity	100% RH at 35c, 95%RH at 40°c
2.5	Shock	20G for 11msc



1.0	Mechanical Specifications	
1.1	Coaxial Connector	SMA-Male
1.2	External Body Finish	Body painted black epoxy enamel
1.3	Weight	8g

3.0	Electrical Specifications	
3.1	Frequency Range	DC-18GHz
3.2	Input Power	1.0W
3.3	VSWR	1.15
3.4	Resistance	50(Ω)

PAGE 1 OF 1	DATE MAY 6 th 2000
PROPRIETARY INFORMATION THE INFORMATION CONTAINED IN THIS DOCUMENT IS THE PROPERTY OF RF-LAMBDA. THE HOLDER OF THIS DOCUMENT SHALL KEEP ALL INFORMATION CONTAINED HEREIN CONFIDENTIAL AND SHALL PROTECT SAME IN THE WHOLE OR IN PART FROM DISCLOSURE AND DISSEMINATION OF ALL THIRD PARTIES AND SHALL USE SAME FOR OPERATING AND MAINTENANCE PURPOSES ONLY.	DESIGN RFFC RF-LAMBDA RFFC
 RFST1G18sM Termination	CAD MODEL REVISION 10
www.rflambda.com	ASSEMBLY REVISION V552
RF-LAMBDA	ASSEMBLY NAME RFLV07
SIZE LT	DRAWING NUMBER D05-A
SHEETS 1 OF 1	