

# WR62 Waveguide Termination 12.4 - 18GHz

#### **Features**

- Full band operation
- Low VSWR
- Rugged mechanical configuration

## **Typical Applications**

- Research and Development
- Test and Measurement
- Microwave Subsystems



### Electrical Specifications, $T_A=25$ °C

Parameters	Min.	Тур.	Max.	Units
Frequency Range	12.4		18	GHz
VSWR			1.1	:1
Power Handling			10	w
Waveguide type	WR62			
Flange type	UG1655/U			
Finishing	Conductive Oxidation			


#### **Environmental Specifications**

Operational Temperature (°C)	-20 to +60	
Storage Temperature (°C)	-55 to +125	
Altitude	30,000 ft. (Epoxy Sealed Controlled environment)	
	60,000 ft. 1.0psi min (Hermetically Sealed Un-controlled environment) (Optional)	
Vibration	25g RMS (15 degrees 2KHz) endurance, 1 hour per axis	
Humidity	100% RH at 35c, 95%RH at 40 deg c	
Shock	20G for 11msec half sine wave, 3 axis both directions	



## **Outline Drawing:**

All Dimensions in mm [inches]



#### **Important Notice**

The information contained herein is believed to be reliable. RF-Lambda makes no warranties regarding the information contained herein. RF-Lambda assumes no responsibility or liability whatsoever for any of the information contained herein. RF-Lambda assumes no responsibility or liability whatsoever for the use of the information contained herein. The information contained herein is provided "AS IS, WHERE IS" and with all faults, and the entire risk associated with such information is entirely with the user. All information contained herein is subject to change without notice. Customers should obtain and verify the latest relevant information before placing orders for RF-Lambda products. The information contained herein or any use of such information does not grant, explicitly or implicitly, to any party any patent rights, licenses, or any other intellectual property rights, whether with regard to such information itself or anything described by such information.

RF-Lambda products are not warranted or authorized for use as critical components in medical, life-saving, or life sustaining applications, or other applications where a failure would reasonably be expected to cause severe personal injury or death.