

SPECIFICATION SHEET**JFW MODEL 50R-401****ROTARY ATTENUATOR**

JFW Industries, Inc.
Phone: 317-887-1340
sales@jfwindustries.com
www.jfwindustries.com

Frequency Range	DC-8 GHz
Impedance	50 Ohms nominal
Attenuation Range	0-60 dB in 10 dB steps
VSWR	1.3:1 maximum DC-4 GHz 1.6:1 maximum 4-8 GHz
Insertion Loss	0.7 dB maximum
Attenuation Accuracy	± 0.5 dB or 2% DC-4 GHz ± 1.0 dB or 3% 4-8 GHz (whichever is greater)
RF Input Power	2 Watts average @ 25°C Derate to 1 Watt average @ 50°C
Peak Power	200 Watts peak (5 uSec, 0.5% duty cycle)
Direction of Rotation	Attenuation increases in a Clockwise direction
Indexing	36 degrees with stop between minimum and maximum settings
RF Connector	SMA female
Operating Temperature Range	0°C to +50°C
Physical Size	See outline drawing 092-5898

ECR/ECN #	DATE	REV	APPR / DATE	ECR/ECN #	DATE	REV	APPR / DATE
	09/16/2008		TRS 09/16/2008				
28192	10/17/2017	A	TRS 10/17/2017				