



RF-LAMBDA

LEADER OF RF BROADBAND SOLUTIONS

RFPLT06G06G

Narrow Band Power Limiter 5.39 – 5.49GHz



Note: The photo is for illustration purposes only.
Please refer to the outline drawing.



Features

- Narrow band Operation 5.39-5.49GHz
- Low Insertion Loss
- High Power Handling. Capability up to 6W
- Customization available upon request

Typical Applications

- Wireless Infrastructure
- Test and Measurement
- Military and Aerospace

Electrical Specifications, $T_A=25\text{ }^{\circ}\text{C}$

Parameter	Min.	Typ.	Max.	Units
Frequency Range	5.39		5.49	GHz
CW Input Power			6	W
Peak Power :Pulse Width 1~20us Pulse Repeat Rate: 100Hz~1500Hz Off period between two pulse: 3ms			250	W
Insertion Loss		0.5	0.7	dB
VSWR		1.2	1.3	: 1
Flat Leakage		18	21	dBm
Peak Power Leakage			30	dBm
Weight	/			Ounces
Input / Output Connectors	(SMA - Female / SMA – Male) - Removable			
Material	Aluminum			
Finish	Gold Plated			

Narrow Band Power Limiter 5.39 – 5.49GHz



Environmental Specifications and Test Standards

Parameter	Standard	Description
Operational Temperature	MIL-STD-39016	-45°C~+85°C
Storage Temperature		-55°C~+125°C
Thermal Shock		1 Hour@ -45°C → 1 Hour @ +85°C (5 Cycles)
Random Vibration		Acceleration Spectral Density 6 (m/s) Total 92.6 RMS
Electrical & Temperature Burn In		Temperature +85°C for 72 Hours
Shock		1. Weight >20g, 50g half sine wave for 11ms, Speed variation 3.44m/s 2. Weight <=20g, 100g Half sine wave for 6ms, Speed variation 3.75m/s 3. Total 18 times (6 directions, 3 repetitions per direction).
Altitude	MIL-STD-883	Standard: 30,000 Ft (Epoxy Sealed Controlled Environment) Optional: Hermetically Sealed (60,000 ft. 1.0 PSI min)
Hermetically Sealed (Optional)		MIL-STD-883 (For Hermetically Sealed Units)



RF-LAMBDA


LEADER OF RF BROADBAND SOLUTIONS

RFPLT06G06G

Outline Drawing:

All Dimensions in mm [inches]

Tolerance ± 0.1 [0.004]



Important Notice

The information contained herein is believed to be reliable. RF-Lambda makes no warranties regarding the information contained herein. RF-Lambda assumes no responsibility or liability whatsoever for any of the information contained herein. RF-Lambda assumes no responsibility or liability whatsoever for the use of the information contained herein. The information contained herein is provided "AS IS, WHERE IS" and with all faults, and the entire risk associated with such information is entirely with the user. All information contained herein is subject to change without notice. Customers should obtain and verify the latest relevant information before placing orders for RF-Lambda products. The information contained herein or any use of such information does not grant, explicitly or implicitly, to any party any patent rights, licenses, or any other intellectual property rights, whether with regard to such information itself or anything described by such information. RF-Lambda products are not warranted or authorized for use as critical components in medical, life-saving, or life sustaining applications, or other applications where a failure would reasonably be expected to cause severe personal injury or death.

Narrow Band Power Limiter 5.39–5.49GHz