



RF-LAMBDA

LEADER OF RF BROADBAND SOLUTIONS

RFAPLT02G08G

2-8GHz Front End Input Over Drive Protection Module



Features

- Wide Band operation 2-8GHz
- Active, High Isolation Limiter
- Low Insertion Loss and Good Return Loss
- High Power Handling Capability up to 1W
- Customization available upon request

Electrical Specifications, $T_A=25^\circ\text{C}$, $V_{dd}=+5\text{V}$.

Parameters	Min.	Typ.	Max.	Units
Frequency Range	2		8	GHz
CW Input Power		1		CW
Peak Power (<10% <2us)		1		W
Insertion Loss		1.3	1.8	dB
VSWR		1.4	1.5	: 1
Flat Leakage @ Pin ≤ 30 dBm		-17	-15	dBm
Peak Power Leakage Pin ≤ 33 dBm (<10% <2us)		-14	-12	dBm
Operating Temperature	-45 to 85			$^\circ\text{C}$
Weight	2.47			ounces
Input / Output Connectors	SMA-Female			
Material	Aluminum			
Finishing	Nickel Plating			

Environmental Specifications


Operational Temperature	-45 to +85 $^\circ\text{C}$
Storage Temperature	-55 to +125 $^\circ\text{C}$
Altitude	30,000 ft. (Epoxy Sealed Controlled Environment)
	60,000 ft 1.0psi min (Hermetically Sealed Un-controlled Environment) (Optional)
Vibration	25g RMS (15 degree 2KHz) endurance, 1 hour per axis
Humidity	100% RH at 35 $^\circ\text{C}$, 95%RH at 40 $^\circ\text{C}$
Shock	20G for 11 msec half sine wave, 3 axis both directions

2-8GHz Front End Input Over Drive Protection Module




Typical Performance Plots


Insertion Loss




Input VSWR




Output VSWR




Isolation




Power Output VS Power Input



Limiting Speed



Recovery Time





RF-LAMBDA


LEADER OF RF BROADBAND SOLUTIONS

RFAPLT02G08G

Outline Drawing:

All Dimensions in mm [inches]

Tolerance ± 0.1 [0.0039]



Important Notice

The information contained herein is believed to be reliable. RF-Lambda makes no warranties regarding the information contained herein. RF-Lambda assumes no responsibility or liability whatsoever for any of the information contained herein. RF-Lambda assumes no responsibility or liability whatsoever for the use of the information contained herein. The information contained herein is provided "AS IS, WHERE IS" and with all faults, and the entire risk associated with such information is entirely with the user. All information contained herein is subject to change without notice. Customers should obtain and verify the latest relevant information before placing orders for RF-Lambda products. The information contained herein or any use of such information does not grant, explicitly or implicitly, to any party any patent rights, licenses, or any other intellectual property rights, whether with regard to such information itself or anything described by such information. RF-Lambda products are not warranted or authorized for use as critical components in medical, life-saving, or life sustaining applications, or other applications where a failure would reasonably be expected to cause severe personal injury or death.

2-8GHz Front End Input Over Drive Protection Module