

SPECIFICATION SHEET**JFW MODEL 50PD-765****4 WAY REACTIVE POWER DIVIDER/COMBINER**

JFW Industries, Inc.
Phone: 317-887-1340
sales@jfwindustries.com
www.jfwindustries.com

Frequency Range	500-6000 MHz
Impedance	50 Ohms nominal
VSWR	1.6:1 maximum < 1.5:1 typical (divider port) < 1.3:1 typical (combiner ports)
Insertion Loss (above 6 dB split)	2.2 dB maximum 0.4 dB typical @ 500 MHz 1.5 dB typical @ 6000 MHz
Amplitude Tracking	± 0.6 dB maximum ± 0.1 dB typical
Phase Tracking	± 6° maximum ± 2° typical
Isolation	17 dB minimum 500-700 MHz 18 dB minimum 700-6000 MHz > 18 dB typical @ 500-700 MHz > 20 dB typical @ 700-6000 MHz
Matched Input Power	5 Watts average (divider port) 0.25 Watts average (combiner ports)
Operating Temperature Range	-40°C to +85°C
RF Connector	SMA female
Physical Size	See outline drawing 092-7218

ECR/ECN #	DATE	REV	APPR / DATE	ECR/ECN #	DATE	REV	APPR / DATE
	05/16/2012		TRS 05/16/2012				
21942	09/28/2012	A	TRS 09/28/2012				
27741	04/27/2017	B	TRS 04/27/2017				