

SPECIFICATION SHEET**JFW MODEL 50PD-848****8 WAY REACTIVE POWER DIVIDER/COMBINER**

JFW Industries, Inc.
Phone: 317-887-1340
sales@jfwindustries.com
www.jfwindustries.com

Frequency Range 350-6000 MHz

Impedance 50 Ohms nominal

VSWR 1.8:1 maximum 350-500 MHz
1.6:1 maximum 500-6000 MHz

1.5:1 typical 350-500 MHz (divider port)
1.4:1 typical 500-6000 MHz (divider port)
1.3:1 typical 350-6000 MHz (combiner ports)

Insertion Loss 3.0 dB maximum
(above 9 dB split) 0.5 dB typical @ 350 MHz
2.6 dB typical @ 6000 MHz

Amplitude Tracking ± 0.8 dB maximum
 ± 0.2 dB typical

Phase Tracking $\pm 9^\circ$ maximum
 $\pm 3^\circ$ typical

Isolation 10 dB minimum 350-500 MHz
18 dB minimum 500-6000 MHz

11.5 dB typical @ 350 MHz
14.0 dB typical @ 400 MHz
19.6 dB typical @ 500 MHz
23.0 dB typical @ > 500 MHz

Matched Input Power 10 Watts average (divider port)
0.25 Watts average (combiner ports)

Temperature Range -40°C to +85°C (operating)
-55°C to +125°C (storage)

RF Connector SMA female

Physical Size See outline drawing 092-9161

ECR/ECN #	DATE	REV	APPR / DATE	ECR/ECN #	DATE	REV	APPR / DATE
	09/05/2018		TRS 09/05/2018				