

SPECIFICATION SHEET**JFW MODEL 75DR-018****DUAL ROTARY ATTENUATOR**

JFW Industries, Inc.
Phone: 317-887-1340
sales@jfwindustries.com
www.jfwindustries.com

Frequency Range	DC-1000 MHz
Impedance	75 Ohms nominal
Attenuation Range	0-30 dB in 1 dB steps
VSWR	1.4:1 maximum DC-500 MHz 1.5:1 maximum 500-1000 MHz
Insertion Loss	0.5 dB maximum
Attenuation Accuracy	± 0.4 dB (1 dB steps) ± 0.5 dB (10 dB steps)
RF Input Power	1 Watt average 1000 Watts peak
Direction of Rotation	Attenuation increases in a Clockwise direction
Indexing	30 degrees with stops at Minimum and maximum
RF Connector	BNC or F female
Operating Temperature Range	-20°C to +85°C
Lifetime	500,000 attenuation steps (each knob)
Knob/Panel Mounting Drawing	092-8435-02
Outline Drawing	092-2135 (75DR-018 BNC)

ECR/ECN #	DATE	REV	APPR / DATE	ECR/ECN #	DATE	REV	APPR / DATE
9999	05/15/2003	A	BAC 03/15/2004	23479	11/26/2013	E	TRS 11/27/2013
20324	07/13/2011	C	TRS 07/13/2011	25776	09/28/2015	F	TRS 09/29/2015
22562	02/25/2013	D	TRS 02/25/2013	28157	10/05/2017	G	TRS 10/05/2017