

SPECIFICATION SHEET**JFW MODEL 75DR-028****DUAL ROTARY ATTENUATOR**

JFW Industries, Inc.
Phone: 317-887-1340
sales@jfwindustries.com
www.jfwindustries.com

Frequency Range	DC-1218 MHz
Impedance	75 Ohms nominal
Attenuation Range	0-11 dB in 0.1 dB steps
VSWR	1.5:1 maximum
Insertion Loss	1.00 dB typical / 1.25 dB maximum
Attenuation Accuracy	± 0.05 dB (0.1 dB steps) ± 0.30 dB (1.0 dB steps)
RF Input Power	1 Watt average 1000 Watts peak
Direction of Rotation	Attenuation increases in a Clockwise direction
Indexing	30 degrees with stops at Minimum and maximum
RF Connector	BNC, F or N female
Operating Temperature Range	-20°C to +85°C
Lifetime	500,000 attenuation steps (each knob)
Knob/Panel Mounting Drawing	092-8435-02
Physical Size	See outline drawing 092-2135

ECR/ECN #	DATE	REV	APPR / DATE	ECR/ECN #	DATE	REV	APPR / DATE
	06/26/2015		BAC 06/26/2015				
28157	10/05/2017	A	TRS 10/05/2017				