SPECIFICATION SHEET

JFW MODEL 50BR-009

BENCH TOP ROTARY ATTENUATOR

JFW Industries, Inc. Phone: 317-887-1340 sales@jfwindustries.com www.jfwindustries.com

Frequency Range DC-1000 MHz

Impedance 50 Ohms nominal

Attenuation Range 0-110 dB in 1 dB steps

VSWR 1.3:1 maximum

Attenuation Accuracy ± 0.5 dB or 2%

(whichever is greater)

Insertion Loss 1.2 dB maximum

RF Input Power 2 Watts average

1000 Watts peak

Direction of Rotation Attenuation increases in a Clockwise

direction

Indexing 30 degrees with stops at

Minimum and maximum

RF Connector BNC, SMA or N female

Operating Temperature Range -20°C to +85°C

Lifetime 500,000 attenuation steps (each knob)

Physical Size See outline drawing 092-3702 (SMA)

ECR/ECN	# DATE	REV	APPR / DATE	ECR/ECN	# DATE	REV	APPR / DATE
9999	05/14/2003	A	TRS 02/24/2004	28157	10/05/2017	D	TRS 10/05/2017
14766	09/25/2007	В	TRS 09/25/2007				
19726	02/22/2011	С	TRS 02/22/2011				

Page 1 of 1 JFW FORM E-7-F REV F