



WAVEGUIDE WR340 DIRECTIONAL COUPLER – RWGCP340SA



1.0	Mechanical Specifications	
1.1	Waveguide type	Rectangular Waveguide WR340
1.2	Flange type	UG435B/U
1.3	Flange Holes	Through
1.4	Basis-material	Alloyed Aluminum
1.5	Internal Body Finish	Silver Plated chromate or conversion
1.6	External Body Finish	Body painted with gray/black epoxy enamel

2.0	Environment specifications	
2.1	Operation Temp.	-54°C~+71°C
2.2	Storage Temp.	-60°C~+125°C
2.3	Altitude	45000 ft
2.4	Vibration	10g rms (15 degree 2KHz)
2.5	Humidity	100% RH at 35c, 95%RH at 40 deg c
2.6	Shock	20G for 11msc

Electrical Specifications						
Frequency Range	Forward Power	Insertion Loss	Coupling	VSWR (master)	VSWR (2 nd Line)	Direction
2.2 – 3.3GHz	1000W	0.15dB	20dB +/- 1.0	1.08:1(Max)	1.3:1(Max)	35dB

PAGE	OF	DATE
		Apr 18 th 2007
PROPRIETARY INFORMATION THE INFORMATION CONTAINED IN THIS DOCUMENT IS THE PROPERTY OF RF-LAMBDA EXCEPT AS SPECIFICALLY AUTHORIZED IN WRITINGS BY RF-LAMBDA. THE HOLDER OF THIS DOCUMENT SHALL KEEP ALL INFORMATION CONTAINED HEREIN CONFIDENTIAL AND SHALL PROTECT SAME IN THE WHOLE OR IN PART FROM DISCLOSURE AND DISSEMINATION OF ALL THIRD PARTIES AND SHALL USE SAME FOR OPERATING AND MAINTENANCE PURPOSES ONLY		DESIGN
		RFPC
		RFPC
		RFPC
 RWGCP340SA WAVEGUIDE COUPLER		CAD MODEL REVISION
		0-4
		ASSEMBLY REVISION
		VS2DS
www.rflambda.com		ASSEMBLY NAME
		RFLVR011
RF-LAMBDA		DRAWING NUMBER
		D02-1
SIZE	SHEETS	OF
LT	1	1