




WAVEGUIDE WR90 CROSSGUIDE DIRECTIONAL COUPLER -RWGCP90SE

3.0	Electrical Specifications	
3.1	Frequency Range	8.5~9.6GHz
3.2	Coupling	60dB
3.3	Directivity	18dB min
3.4	VSWR	1.5
3.5	Insertion Loss	0.2dB max.
3.6	Average Power	1000W

1.0	Mechanical Specifications	
1.1	Waveguide type	Rectangular WR90
1.2	Flange type	CPRG, CPRF, COVER, CHOKE available
1.3	Flange Holes	Through
1.4	Basis-material	Alloyed Cuprum
1.5	Internal Body Finish	Plated chromate or conversion
1.6	External Body Finish	Body painted with gray/black epoxy enamel

2.0	Environment specifications	
2.1	Operation Temp.	-40°C~+85°C
2.2	Storage Temp.	-60°C~+125°C
2.3	Altitude	45000 ft
2.4	Vibration	10g rms (15 degree 2KHz)
2.5	Humidity	100% RH at 35c, 95%RH at 40 deg c
2.6	Shock	20G for 11msc

PAGE OF		DATE Jul 9 th 2008
PROPRIETARY INFORMATION THE INFORMATION CONTAINED IN THIS DOCUMENT IS THE PROPERTY OF RF-LAMBDA EXCEPT AS SPECIFICALLY AUTHORIZED IN WRITING BY RF-LAMBDA. THE HOLDER OF THIS DOCUMENT SHALL KEEP ALL INFORMATION CONTAINED HEREIN CONFIDENTIAL AND SHALL PROTECT SAME IN THE WHOLE OR IN PART FROM DISCLOSURE AND DISSEMINATION OF ALL THIRD PARTIES AND SHALL USE SAME FOR OPERATING AND MAINTENANCE PURPOSES ONLY  RWGCP90SE WAVEGUIDE COUPLER www.rflambda.com		DESIGN
		RFPC
		RFPC
		CAD MODEL REVISION 1-4
		ASSEMBLY REVISION VS20-3
		ASSEMBLY NAME RFLVR04
		DRAWING NUMBER D02-5
RF-LAMBDA		SIZE LT SHEETS 1 OF 1