

WR28 Waveguide "I" Shape 360 Degrees Dual Channel Rotary Joint 33 - 36GHz

Features

- Dual Channel "I" shape Rotary Joint.
- Low Insertion Loss.



Typical Applications

- Radar Applications
- Research and Development
- Directional Antenna Feed

Electrical Specifications, $T_A=25\,^{\circ}\!\!C$

Parameters	CH1			CH ₂			
	Min.	Тур.	Max.	Min.	Тур.	Max.	Units
Frequency Range	33		36	33		36	GHz
VSWR			1.35			1.5	:1
VSWR WOW			0.05			0.1	
Insertion Loss			0.5			0.5	dB
Insertion Loss WOW			0.1			0.1	dB
Average Power	30						W
Peak Power	0.3					KW	
Max. RPM	240						
Rotations life cycle	5000000						
Waveguide Type	WR28						
Flange Type	UG599/U						

Environmental Specifications

Operational Temperature (°C)	-45 to +85		
Storage Temperature (°C)	-55 to +125		
Altitude	45000 ft		
Vibration	10g RMS (15 degrees 2KHz)		
Humidity	100% RH at 35c, 95%RH at 40 °C		
Shock	20G for 11msec		


RF-LAMBDA USA

www.rflambda.com



Outline Drawing:

All Dimensions in mm [inches]



Important Notice

The information contained herein is believed to be reliable. RF-Lambda makes no warranties regarding the information contained herein. RF-Lambda assumes no responsibility or liability whatsoever for any of the information contained herein. RF-Lambda assumes no responsibility or liability whatsoever for the use of the information contained herein. The information contained herein is provided "AS IS, WHERE IS" and with all faults, and the entire risk associated with such information is entirely with the user. All information contained herein is subject to change without notice. Customers should obtain and verify the latest relevant information before placing orders for RF-Lambda products. The information contained herein or any use of such information does not grant, explicitly or implicitly, to any party any patent rights, licenses, or any other intellectual property rights, whether with regard to such information itself or anything described by such information.

RF-Lambda products are not warranted or authorized for use as critical components in medical, life-saving, or life sustaining applications, or

RF-Lambda products are not warranted or authorized for use as critical components in medical, life-saving, or life sustaining applications, or other applications where a failure would reasonably be expected to cause severe personal injury or death.