

U-Band, X2 Active Frequency Multiplier, 40 to 60 GHz, +15 dBm P_{out}

Description:

Model SFA-403603215-VMKF-S1 is an active X2 frequency multiplier. The multiplier has an input frequency of 20 to 30 GHz with a typical input power of +5 dBm and an output frequency of 40 to 60 GHz with a typical output power of +15 dBm. The multiplier also has a typical harmonic suppression of -20 dBc. The DC power requirement for the multiplier is +8 V_{DC}/400 mA. The input port configuration is a female K 2.92 mm connector and the output is male V 1.85 mm connector. Other port configurations are available under different model numbers.



Features:

- Low Harmonic Emission
- High Output Power
- Low Harmonic Components

Applications:

- Frequency Extenders
- Source Module
- Communication Systems

Electrical Specifications:

Parameter	Minimum	Typical	Maximum
Input Frequency	20 GHz		30 GHz
Input Power		+5 dBm	+20 dBm
Output Frequency	40 GHz		60 GHz
Output Power		+15 dBm	
Harmonic Suppression		-20 dBc	
Spurious		-60 dBc	
Port Return Loss		10 dB	
DC Voltage	+6 V _{DC}	+8 V _{DC}	+15 V _{DC}
DC Supply Current		400 mA	
Specification Temperature		+25 °C	
Operating Temperature	0 °C		+50 °C

Mechanical Specifications:


Item	Specification
Input Port	K(F)
Output Port	V(M)
Bias	Solder Pin
Case Material	Aluminum
Finish	Gold Plated
Weight	1.3 Oz
Size	1.20" (W) 1.20" (L) X 0.50" (H)
Outline	BG-SC-1




U-Band, X2 Active Frequency Multiplier, 40 to 60 GHz, +15 dBm P_{out}

Typical Output Power vs. Output Frequency

Bias: +8 V_{DC}/400 mA; Input Power: +5 dBm



Mechanical Outline: (Unless otherwise specified, all dimensions are in inches [millimeters])





U-Band, X2 Active Frequency Multiplier, 40 to 60 GHz, +15 dBm P_{out}

Note:

- All data presented is collected from a sample lot. Actual data may vary unit to unit.
- All testing was performed under +25 °C case temperature.
- SAGE Millimeter, Inc. reserves the right to change the information presented without notice.
- Other mechanical configurations are available under different model numbers.

Caution:

- Exceeding absolute maximum ratings shown will damage the device.
- The device is static sensitive. Always follow ESD rules when working with the device.
- The case temperature of the device shall never exceed +50 °C. Use proper Heatsink or fan if necessary.
- Proper torque, 8.0 ± 0.15 inch-pounds (0.90 ± 0.02 Nm), should be applied. **SAGE Millimeter torque wrench, model SCH-08008-S1, is highly recommended.**

