
SOL-24318-42-G1

Rev. 1.0

K-Band Volume Production Oscillator

Description:

Model SOL-24318-42-G1 is a volume-production ready, K Band Gunn oscillator that utilizes a high performance GaAs Gunn diode and high Q cavity to achieve excellent phase noise and power stability. The oscillator is designed for fixed frequency applications, however, the frequency can be adjusted by ±1.0 GHz using the self-locking set screw provided.



Features:

- Low Cost and Production Ready
- Mechanical tuning ability
- Low AM/FM Noise and Harmonics
- High Frequency and Power Stability

Applications:

- Traffic Control Systems
- Communication Systems
- Radar Systems

Electrical Specifications:

Parameter	Minimum	Typical	Maximum
Center Frequency		24.125 GHz	
Power Output	+17 dBm	+18 dBm	
Mechanical Tuning Range	±500 MHz	±1,000 MHz	
Harmonic Emissions		-20 dBc	
Phase Noise @ 100 KHz offset		-98 dBc/Hz	
Frequency Stability			-0.8 MHz/°C
Power Output Stability			-0.02 dB/°C
Bias Voltage		+6 V_{DC}	+6.5 V_{DC}
Bias Current		650 mA	
Specification Temperature		+25 ˚C	
Operating Temperature	-40 ˚C		+85 ˚C

Mechanical Specifications:


Item	Specification
RF Port	WR-42 Waveguide with UG-595/U Flange
Cavity Material	Die Casted Zinc
Finish	Chem Film
Weight	1 Oz
Outline	OL-K1

www.sagemillimeter.com | 3043 Kashiwa Street, Torrance, CA 90505
Phone: 424-757-0168 | Fax: 424-757-0188 | Email: sales@sagemillimeter.com

Copyright © 2018 by SAGE Millimeter, Inc.

K-Band Volume Production Oscillator

Mechanical Outline: (Unless otherwise specified, all dimensions are in inches [millimeters])



Note:

- SAGE Millimeter, Inc. reserves the right to change the information presented without notice.

Caution:

- Reversing polarity bias will destroy the device.
- Exceeding absolute maximum ratings shown will damage the device.
- The device is static sensitive. Always follow ESD rules when working with the device.
- Any foreign objects in the waveguide will cause performance degradation and possible device damage.
- The case temperature of the device shall never exceed **+85˚C**. Use an additional heatsink or fan if necessary.

www.sagemillimeter.com | 3043 Kashiwa Street, Torrance, CA 90505
Phone: 424-757-0168 | Fax: 424-757-0188 | Email: sales@sagemillimeter.com

Copyright © 2018 by SAGE Millimeter, Inc.