
STA-06-22-F2

Rev. 1.2

Q-Band Fixed Attenuator, 6 dB

Description:

Model STA-06-22-F2 is a 6 dB fixed attenuator that is used in millimeterwave systems and operates from 33 to 50 GHz. The attenuator has a fixed attenuation value of 6 dB at center frequency, 41.5 GHz. While the attenuator is designed and fabricated for full waveguide band applications, the attenuation value of this model does show a minor slope within the band due to its distinct mechanical configuration. Various attenuation values are available under different model numbers.



Features:

- Full Band Coverage
- Low Cost
- Accurate Attenuation Value at Center Frequency

Applications:

- Test Lab
- Instrumentations
- System Integration

Electrical Specifications:

Parameter	Minimum	Typical	Maximum
RF Frequency Range	33 GHz		50 GHz
Attenuation @ 41.5 GHz		6.0 dB	
Return Loss		21 dB	
Power Handling		500 mW	750 mW
Specification Temperature		+25˚C	
Operating Temperature	-40˚C		+85˚C

Mechanical Specifications:


Item	Specification
RF Input	WR-22 Waveguide with UG-383/U Flange
RF Output	WR-22 Waveguide with UG-383/U Flange
Setting	Fixed
Insertion Length	3.50”
Finish	Gold Plated Waveguide Faces; Black Painted Body
Weight	2.5 Oz
Outline	TA-FQ-BX1

www.sagemillimeter.com | 3043 Kashiwa Street, Torrance, CA 90505
Phone: 424-757-0168 | Fax: 424-757-0188 | Email: sales@sagemillimeter.com


Copyright © 2016 by SAGE Millimeter, Inc.

Q-Band Fixed Attenuator, 6 dB

Typical Attenuation vs. Frequency



Mechanical Outline: (Unless otherwise specified, all dimensions are in inches [millimeters])



Note:

- All data presented is collected from a sample lot. Actual data may vary unit to unit, slightly.
- All testing was performed under +25°C case temperature.
- SAGE Millimeter, Inc. reserves the right to change the information presented without notice.

www.sagemillimeter.com | 3043 Kashiwa Street, Torrance, CA 90505
Phone: 424-757-0168 | Fax: 424-757-0188 | Email: sales@sagemillimeter.com

Copyright © 2016 by SAGE Millimeter, Inc.

Q-Band Fixed Attenuator, 6 dB

Caution:

- RF power should never exceed 750 mW.
- Any foreign objects in the waveguide will cause performance degradation and may damage the device.

SAGE Millimeter, Inc.

SAGE Millimeter, Inc.

www.sagemillimeter.com | 3043 Kashiwa Street, Torrance, CA 90505
Phone: 424-757-0168 | Fax: 424-757-0188 | Email: sales@sagemillimeter.com

Copyright © 2016 by SAGE Millimeter, Inc.