SWI-22046-SB

Rev. 1.0

WR-22 Waveguide Spacer, 46 Mils, 1/8 λg

Description:



SWI-22046-SB is a 0.046” thick, 1/8 wavelength, instrumentation grade Q Band waveguide spacer (shim) with WR-22 window and UG-383/U circular flange. The spacer is manufactured with a precision machining process to ensure high quality and ruggedness. The spacer is offered to cover the frequency range of 33 to 50 GHz.

Features:

- Frequency Range: 33 to 50 GHz
- 1/8 Wavelength
- Low Insertion Loss
- Instrumentation Grade


Applications:

- Module Tuning
- Sub-assemblies
- Mechanical Fitting
- VNA Calibration

Mechanical Specifications:

Item	Specification
Waveguide Size	WR-22 Waveguide with UG-383/U Flange
Material	Brass
Finish	Gold Plated
Weight	0.3 Oz
Insertion Length	0.046”(L)
Outline	WI-QL

Mechanical Outline: (Unless otherwise specified, all dimensions are in inches [millimeters])



Note:

- Length "L" is customizable.
- SAGE Millimeter, Inc. reserves the right to change the information presented without notice.

www.sagemillimeter.com | 3043 Kashiwa Street, Torrance, CA 90505
Phone: 424-757-0168 | Fax: 424-757-0188 | Email: sales@sagemillimeter.com

Copyright © 2018 by SAGE Millimeter, Inc.

SAGE Millimeter, Inc.