P/N:DBLNA200200400A

QOTANA TECHNOLOGIES Ultra Wide Band Low Noise Amplifier 0.2GHz~4GHz

Features

- Gain: 13dB Typical
- Noise Figure: 2.5dB Typical
- P1dB Output Power: +21dBm Typical
- Supply Voltage: +5V
- 50 Ohm Matched



Typical Applications

- Wireless Infrastructure
- Military & Aerospace
- Fiber Optics

RF Microwave & VSAT
Test Instrument

Parameter	Min.	Typ.	Max.	Min.	Typ.	Max.	Units
Frequency Range	0.2		1.5	1.5		4	GHz
Gain	10	14		8	13		dB
Gain Flatness		±1.5	±2.5		±2.5	±3.5	dB
Gain Variation Over Temperature (-45℃~+85℃)		±0.5			±0.5		dB
Noise Figure		2.5	4.0		2.3	3.0	dB
Input VSWR		2.0	3.0		1.5	2.0	: 1
Output VSWR		1.5	2.0		1.5	2.0	: 1
Output 1dB Compression Point (P1dB)	20	21		20	22		dBm
Saturated Output Power (Psat)		22			23		dBm
Output Third Order Intercept (IP3)		36			36		dBm
Supply Current (Vdd=+5V)		110	120		110	120	mA
Isolation S12		-20			-20		dB

Weight	1.06 ounces	Impedance	50 ohms
Input /Output Connector	SMA-Female	Material	Aluminum
Finishing	Standard: Gold 40 micron; Nickel 220 micron thickness	Package Sealing	Epoxy Sealing (Standard)
	Option: Gold 80 micron; Nickel 180 micron thickness		Hermetically Sealed (Option with extra charge)

QOTANA TECHNOLOGIES Ultra Wide Band Low Noise Amplifier 0.2GHz~4GHz

Absolute Maximum Ratings

Operating Voltage	+5.5V
RF Input Power (RFIN)	+15dBm

Biasing Up Procedure

Step 1	Connect Ground Pin
Step 2	Connect input and output
Step 3	Connect +5V biasing

Power OFF Procedure


Step 1	Turn off +5V biasing
Step 2	Remove RF connection
Step 3	Remove Ground

Environmental Specifications

Operational Temperature	-45ºC~+85ºC
Storage Temperature	-55ºC~+125ºC
Altitude	30,000 ft. (Epoxy Sealed Controlled environment)
	60,000 ft. 1.0psi min (Hermetically Sealed Un-controlled environment) (Optional)
Vibration	25g RMS (15 degrees 2KHz) endurance, 1 hour per axis
Humidity	100% RH at 35c, 95%RH at 40ºc
Shock	20G for 11msec half sine wave,3 axis both directions

Outline Drawing:


All Dimensions in mm (inches) Heat Sink required during operation(Sold Seperately)




P/N:DBLNA200200400A

QOTANA TECHNOLOGIES Ultra Wide Band Low Noise Amplifier 0.2GHz~4GHz


Gain @+25℃




Input VSWR @+25℃




Output VSWR @+25℃




Isolation @+25℃




Gain @-45℃




Input VSWR @-45℃



Output VSWR @-45℃




Isolation @-45℃




QOTANA TECHNOLOGIES

Ultra Wide Band Low Noise Amplifier 0.2GHz~4GHz


Gain @+85℃




Input VSWR @+85℃




Output VSWR @+85℃




Isolation @+85℃




Gain vs. Output Power




P1dB vs. Frequency



Output Third Order Intercept (IP3)




Noise Figure




QOTANA TECHNOLOGIES Ultra Wide Band Low Noise Amplifier 0.2GHz~4GHz


2nd Harmonic Wave Output Power



3rd Harmonic Wave Output Power



4th Harmonic Wave Output Power



QOTANA TECHNOLOGIES and its affiliates reserve the right to make changes to the product(s) or information contained herein without notice. Visit www.qotana.com for additional data sheets and product information.