



RF Power LDMOS Transistor

N-Channel Enhancement-Mode Lateral MOSFET

The 250 W CW RF power transistor is designed for industrial, scientific, medical (ISM) and industrial heating applications at 2450 MHz. This device is suitable for use in CW, pulse and linear applications. This high gain, high efficiency rugged device is targeted to replace industrial magnetrons and will provide longer life and easier servicing.

Typical Performance: In 2400–2500 MHz reference circuit, $V_{DD} = 32$ Vdc

| Frequency (MHz) | Signal Type | P_{in} (W) | G_{ps} (dB) | η_D (%) | P_{out} (W) |
|-----------------|-------------|--------------|---------------|--------------|---------------|
| 2400 | CW | 9.0 | 14.5 | 55.5 | 255 |
| 2450 | | 9.0 | 14.7 | 54.8 | 263 |
| 2500 | | 9.0 | 14.3 | 55.5 | 242 |

Load Mismatch/Ruggedness

| Frequency (MHz) | Signal Type | VSWR | P_{in} (W) | Test Voltage | Result |
|-----------------|-------------|-------------------------------|------------------------|--------------|-----------------------|
| 2450 | CW | > 10:1 at all Phase Angles | 14 (3 dB Overdrive) | 32 | No Device Degradation |

Features

- Characterized with series equivalent large-signal impedance parameters
- Internally matched for ease of use
- Qualified up to a maximum of 32 V_{DD} operation
- Integrated high performance ESD protection

Typical Applications


- Industrial heating and drying
- Material welding
- Plasma lighting
- Scientific
- Medical: skin treatment, blood therapy, electrosurgery

MRF7S24250N

**2450 MHz, 250 W, 32 V
 RF POWER LDMOS TRANSISTOR**



**OM-780-2L
 PLASTIC**



(Top View)

Note: Exposed backside of the package is the source terminal for the transistor.

Figure 1. Pin Connections

Table 1. Maximum Ratings

| Rating | Symbol | Value | Unit |
|--|-----------|-------------|-----------|
| Drain-Source Voltage | V_{DSS} | -0.5, +65 | Vdc |
| Gate-Source Voltage | V_{GS} | -6.0, +10 | Vdc |
| Storage Temperature Range | T_{stg} | -65 to +150 | °C |
| Case Operating Temperature Range | T_C | -40 to +150 | °C |
| Operating Junction Temperature Range (1,2) | T_J | -40 to +225 | °C |
| Total Device Dissipation @ $T_C = 25^\circ\text{C}$ Derate above 25°C | P_D | 769 3.85 | W W/°C |

Table 2. Thermal Characteristics

| Characteristic | Symbol | Value (2,3) | Unit |
|---|-----------------|-------------|------|
| Thermal Resistance, Junction to Case CW: Case Temperature 98°C, 250 W CW, $I_{DQ} = 100\text{ mA}$, 2450 MHz | $R_{\theta JC}$ | 0.26 | °C/W |
| Thermal Impedance, Junction to Case Pulse: Case Temperature 53°C, 250 W Peak, 100 μsec Pulse Width, 10% Duty Cycle, $I_{DQ} = 100\text{ mA}$, 2450 MHz | $Z_{\theta JC}$ | 0.024 | °C/W |

Table 3. ESD Protection Characteristics

| Test Methodology | Class |
|---------------------------------------|-------------------|
| Human Body Model (per JESD22-A114) | 2, passes 2500 V |
| Machine Model (per EIA/JESD22-A115) | B, passes 250 V |
| Charge Device Model (per JESD22-C101) | IV, passes 2000 V |

Table 4. Moisture Sensitivity Level

| Test Methodology | Rating | Package Peak Temperature | Unit |
|--------------------------------------|--------|--------------------------|------|
| Per JESD22-A113, IPC/JEDEC J-STD-020 | 3 | 260 | °C |

Table 5. Electrical Characteristics ($T_A = 25^\circ\text{C}$ unless otherwise noted)

| Characteristic | Symbol | Min | Typ | Max | Unit |
|----------------|--------|-----|-----|-----|------|
|----------------|--------|-----|-----|-----|------|

Off Characteristics

| | | | | | |
|---|-----------|---|---|----|-----------------|
| Zero Gate Voltage Drain Leakage Current ($V_{DS} = 65\text{ Vdc}$, $V_{GS} = 0\text{ Vdc}$) | I_{DSS} | — | — | 10 | μAdc |
| Zero Gate Voltage Drain Leakage Current ($V_{DS} = 32\text{ Vdc}$, $V_{GS} = 0\text{ Vdc}$) | I_{DSS} | — | — | 2 | μAdc |
| Gate-Source Leakage Current ($V_{GS} = 5\text{ Vdc}$, $V_{DS} = 0\text{ Vdc}$) | I_{GSS} | — | — | 1 | μAdc |

On Characteristics

| | | | | | |
|---|--------------|-----|-----|-----|-----|
| Gate Threshold Voltage ($V_{DS} = 10\text{ Vdc}$, $I_D = 303\ \mu\text{Adc}$) | $V_{GS(th)}$ | — | 1.2 | — | Vdc |
| Gate Quiescent Voltage ($V_{DD} = 30\text{ Vdc}$, $I_D = 100\text{ mAdc}$, Measured in Functional Test) | $V_{GS(Q)}$ | 1.1 | 1.6 | 2.1 | Vdc |
| Drain-Source On-Voltage ($V_{GS} = 10\text{ Vdc}$, $I_D = 3.7\text{ Adc}$) | $V_{DS(on)}$ | — | 0.2 | — | Vdc |

Dynamic Characteristics (4)

| | | | | | |
|---|-----------|---|-----|---|----|
| Reverse Transfer Capacitance ($V_{DS} = 32\text{ Vdc} \pm 30\text{ mV(rms)ac}$ @ 1 MHz, $V_{GS} = 0\text{ Vdc}$) | C_{rss} | — | 4.3 | — | pF |
|---|-----------|---|-----|---|----|

1. Continuous use at maximum temperature will affect MTTF.
2. MTTF calculator available at <http://www.nxp.com/RF/calculators>.
3. Refer to AN1955, *Thermal Measurement Methodology of RF Power Amplifiers*. Go to <http://www.nxp.com/RF> and search for AN1955.
4. Part internally matched both on input and output.

(continued)


Table 5. Electrical Characteristics ($T_A = 25^\circ\text{C}$ unless otherwise noted) (continued)

| Characteristic | Symbol | Min | Typ | Max | Unit |
|---|-----------|-----|-------|------|------|
| Functional Tests (In NXP Test Fixture, 50 ohm system) $V_{DD} = 30\text{ Vdc}$, $I_{DQ} = 100\text{ mA}$, $P_{in} = 9\text{ W Peak}$ (0.9 W Avg.), $f = 2450\text{ MHz}$, 100 μsec Pulse Width, 10% Duty Cycle | | | | | |
| Output Power | P_{out} | 237 | 256 | 319 | W |
| Drain Efficiency | η_D | 48 | 50 | — | % |
| Input Return Loss | IRL | — | -15.0 | -8.5 | dB |

Table 6. Ordering Information

| Device | Tape and Reel Information | Package |
|---------------|---|-----------|
| MRF7S24250NR3 | R3 Suffix = 250 Units, 32 mm Tape Width, 13-inch Reel | OM-780-2L |

TYPICAL CHARACTERISTICS



Note: Each side of device measured separately.

Figure 2. Capacitance versus Drain-Source Voltage

2400–2500 MHz REFERENCE CIRCUIT — 2" × 3" (5.1 cm × 7.6 cm)

Table 7. 2400–2500 MHz Performance (In NXP Reference Circuit, 50 ohm system)


$V_{DD} = 32 \text{ Vdc}$, $I_{DQ} = 100 \text{ mA}$, $T_C = 25^\circ\text{C}$

| Frequency (MHz) | P_{in} (W) | G_{ps} (dB) | η_D (%) | P_{out} (W) |
|-----------------|--------------|---------------|--------------|---------------|
| 2400 | 9.0 | 14.5 | 55.5 | 255 |
| 2450 | 9.0 | 14.7 | 54.8 | 263 |
| 2500 | 9.0 | 14.3 | 55.5 | 242 |

Table 8. Load Mismatch/Ruggedness (In NXP Reference Circuit)

| Frequency (MHz) | Signal Type | VSWR | P_{in} (W) | Test Voltage, V_{DD} | Result |
|-----------------|-------------|----------------------------|------------------------|------------------------|-----------------------|
| 2450 | CW | > 10:1 at all Phase Angles | 14 (3 dB Overdrive) | 32 | No Device Degradation |

2400–2500 MHz REFERENCE CIRCUIT — 2" x 3" (5.1 cm x 7.6 cm)



*C4 and C5 are mounted vertically.

Figure 3. MRF7S24250N Reference Circuit Component Layout — 2400–2500 MHz

Table 9. MRF7S24250N Reference Circuit Component Designations and Values — 2400–2500 MHz

| Part | Description | Part Number | Manufacturer |
|----------------------------|---|--------------------|--------------------|
| C1, C3, C4, C5, C6, C7, C8 | 27 pF Chip Capacitors | ATC600F270JT250XT | ATC |
| C2, C9 | 10 μ F Chip Capacitors | GRM32ER61H106KA12L | Murata |
| C10 | 220 μ F, 50 V Electrolytic Capacitor | 227CKE050M | Illinois Capacitor |
| Q1 | RF Power LDMOS Transistor | MRF7S24250NR3 | NXP |
| R1 | 10 Ω , 1/4 W Chip Resistor | CRCW120610R0FKEA | Vishay |
| PCB | Rogers RT6035HTC, 0.030", $\epsilon_r = 3.66$ | D68993 | MTL |

**TYPICAL CHARACTERISTICS — 2400–2500 MHz
REFERENCE CIRCUIT**




Figure 4. Power Gain, Drain Efficiency and Output Power versus Frequency at a Constant Input Power




Figure 5. Output Power versus Gate-Source Voltage





Figure 6. Power Gain, Drain Efficiency and Input Power versus Output Power and Frequency

2400–2500 MHz REFERENCE CIRCUIT



| f MHz | Z _{source} Ω | Z _{load} Ω |
|----------|--------------------------|------------------------|
| 2400 | 1.76 – j5.76 | 1.49 – j2.45 |
| 2450 | 1.66 – j5.50 | 1.43 – j2.18 |
| 2500 | 1.56 – j5.23 | 1.36 – j1.90 |

Z_{source} = Test circuit impedance as measured from gate to ground.

Z_{load} = Test circuit impedance as measured from drain to ground.




Figure 7. Series Equivalent Source and Load Impedance — 2400–2500 MHz

2450 MHz NARROWBAND PRODUCTION TEST FIXTURE — 3" x 5" (7.6 cm x 12.7 cm)

Table 10. 2450 MHz Narrowband Performance (In NXP Test Fixture, 50 ohm system) $V_{DD} = 30$ Vdc, $I_{DQ} = 100$ mA, $P_{in} = 9$ W Peak (0.9 W Avg.), $f = 2450$ MHz, 100 μ sec Pulse Width, 10% Duty Cycle

| Characteristic | Symbol | Min | Typ | Max | Unit |
|-------------------|-----------|-----|------|-----|------|
| Output Power | P_{out} | — | 256 | — | W |
| Drain Efficiency | η_D | — | 49.0 | — | % |
| Input Return Loss | IRL | — | -17 | -9 | dB |

2450 MHz NARROWBAND PRODUCTION TEST FIXTURE — 3" x 5" (7.6 cm x 12.7 cm)




Figure 8. MRF7S24250N Narrowband Test Circuit Component Layout — 2450 MHz

Table 11. MRF7S24250N Narrowband Test Circuit Component Designations and Values — 2450 MHz

| Part | Description | Part Number | Manufacturer |
|-------------|--|-----------------------|--------------|
| C1, C5, C12 | 10 μ F Chip Capacitors | C5750X7S2A106M230KB | TDK |
| C2, C6, C11 | 3 pF Chip Capacitors | ATC100B3R0CT500XT | ATC |
| C3 | 7.5 pF Chip Capacitor | ATC100B7R5CT500XT | ATC |
| C4 | 1.5 pF Chip Capacitor | ATC100B1R5BT500XT | ATC |
| C7 | 0.3 pF Chip Capacitor | ATC100B0R3BT500XT | ATC |
| C8 | 1.5 pF Chip Capacitor | ATC100B1R5BT500XT | ATC |
| C9, C10 | 8.2 pF Chip Capacitors | ATC100B8R2CT500XT | ATC |
| C13, C14 | 470 μ F, 100 V Electrolytic Capacitors | MCGPR100V477M16X32-RH | Multicomp |
| R1 | 5.9 Ω , 1/4 W Chip Resistor | CRCW12065R90FKEA | Vishay |
| PCB | Taconic RF35, 0.030", $\epsilon_r = 3.5$ | — | MTL |

| f MHz | Z_{source} Ω | Z_{load} Ω |
|----------|--------------------------|------------------------|
| 2450 | 1.96 - j5.61 | 1.55 - j1.76 |

Z_{source} = Test circuit impedance as measured from gate to ground.

Z_{load} = Test circuit impedance as measured from drain to ground.






Figure 9. Narrowband Series Equivalent Source and Load Impedance — 2450 MHz




1. Slot dimensions are minimum dimensions and exclude milling tolerances

Figure 10. PCB Pad Layout for OM-780-2L

PACKAGE DIMENSIONS



| | | |
|--|--------------------------|----------------------------|
| © NXP SEMICONDUCTORS N.V. ALL RIGHTS RESERVED | MECHANICAL OUTLINE | PRINT VERSION NOT TO SCALE |
| TITLE: OM780-2 STRAIGHT LEAD | DOCUMENT NO: 98ASA10831D | REV: C |
| | STANDARD: NON-JEDEC | |
| | SOT1693-1 | 22 JAN 2016 |



BOTTOM VIEW
VIEW G-G

| | | | |
|--|--------------------|----------------------------|-------------|
| © NXP SEMICONDUCTORS N.V. ALL RIGHTS RESERVED | MECHANICAL OUTLINE | PRINT VERSION NOT TO SCALE | |
| TITLE: OM780-2 STRAIGHT LEAD | | DOCUMENT NO: 98ASA10831D | REV: C |
| | | STANDARD: NON-JEDEC | |
| | | SOT1693-1 | 22 JAN 2016 |

NOTES:

1. CONTROLLING DIMENSION: INCH
2. INTERPRET DIMENSIONS AND TOLERANCES PER ASME Y14.5M-1994.
3. DATUM PLANE -H- IS LOCATED AT TOP OF LEAD AND IS COINCIDENT WITH THE LEAD WHERE THE LEAD EXITS THE PLASTIC BODY AT THE TOP OF THE PARTING LINE.
4. DIMENSIONS "D" AND "E1" DO NOT INCLUDE MOLD PROTRUSION. ALLOWABLE PROTRUSION IS .006 PER SIDE. DIMENSIONS "D AND "E1" DO INCLUDE MOLD MISMATCH AND ARE DETERMINED AT DATUM PLANE -H-.
5. DIMENSION b DOES NOT INCLUDE DAMBAR PROTRUSION. ALLOWABLE DAMBAR PROTRUSION SHALL BE .005 TOTAL IN EXCESS OF THE b DIMENSION AT MAXIMUM MATERIAL CONDITION.
6. DATUMS -A- AND -B- TO BE DETERMINED AT DATUM PLANE -H-.
7. DIMENSION A1 APPLIES WITHIN ZONE "J" ONLY
8. HATCHING REPRESENTS THE EXPOSED AREA OF THE HEAT SLUG. THE DIMENSIONS D1 AND E2 REPRESENT THE VALUES BETWEEN THE TWO OPPOSITE POINTS ALONG THE EDGES OF EXPOSED AREA OF HEAT SLUG.

STYLE 1:

- PIN 1 - DRAIN
- PIN 2 - GATE
- PIN 3 - SOURCE

| DIM | INCH | | MILLIMETER | | DIM | INCH | | MILLIMETER | |
|--|----------|------|--------------------|-------|--------------------------|----------------------------|------|-------------|-------|
| | MIN | MAX | MIN | MAX | | MIN | MAX | MIN | MAX |
| A | 0.148 | .152 | 3.76 | 3.86 | b | .497 | .503 | 12.62 | 12.78 |
| A1 | .059 | .065 | 1.50 | 1.65 | c1 | .007 | .011 | 0.18 | 0.28 |
| D | .808 | .812 | 20.52 | 20.62 | e1 | .721 | .729 | 18.31 | 18.52 |
| D1 | .720 | ---- | 18.29 | ---- | | | | | |
| E | .762 | .770 | 19.36 | 19.56 | aaa | .004 | | 0.10 | |
| E1 | .390 | .394 | 9.91 | 10.01 | | | | | |
| E2 | .306 | ---- | 7.77 | ---- | | | | | |
| E3 | .383 | .387 | 9.73 | 9.83 | | | | | |
| F | .025 BSC | | 0.635 BSC | | | | | | |
| © NXP SEMICONDUCTORS N.V. ALL RIGHTS RESERVED | | | MECHANICAL OUTLINE | | | PRINT VERSION NOT TO SCALE | | | |
| TITLE: OM780-2 STRAIGHT LEAD | | | | | DOCUMENT NO: 98ASA10831D | | | REV: C | |
| | | | | | STANDARD: NON-JEDEC | | | | |
| | | | | | SOT1693-1 | | | 22 JAN 2016 | |

PRODUCT DOCUMENTATION, SOFTWARE AND TOOLS

Refer to the following resources to aid your design process.

Application Notes

- AN1907: Solder Reflow Attach Method for High Power RF Devices in Over-Molded Plastic Packages
- AN1955: Thermal Measurement Methodology of RF Power Amplifiers
- AN3789: Clamping of High Power RF Transistors and RFICs in Over-Molded Plastic Packages

Engineering Bulletins

- EB212: Using Data Sheet Impedances for RF LDMOS Devices

White Paper

- RFPLASTICWP: Designing with Plastic RF Power Transistors

Software

- Electromigration MTTF Calculator
- RF High Power Model
- .s2p File

Development Tools

- Printed Circuit Boards

To Download Resources Specific to a Given Part Number:

1. Go to <http://www.nxp.com/RF>
2. Search by part number
3. Click part number link
4. Choose the desired resource from the drop down menu

REVISION HISTORY

The following table summarizes revisions to this document.

| Revision | Date | Description |
|----------|------------|---|
| 0 | Aug. 2015 | <ul style="list-style-type: none">• Initial Release of Data Sheet |
| 1 | Sept. 2016 | <ul style="list-style-type: none">• Table 2, Thermal Characteristics: added Thermal Impedance $Z_{\theta JC}$ data, p. 2• Functional Tests table: table values updated to reflect current test data results. Added Min and Max values, p. 3 |

How to Reach Us:

Home Page:
nxp.com

Web Support:
nxp.com/support

Information in this document is provided solely to enable system and software implementers to use NXP products. There are no express or implied copyright licenses granted hereunder to design or fabricate any integrated circuits based on the information in this document. NXP reserves the right to make changes without further notice to any products herein.

NXP makes no warranty, representation, or guarantee regarding the suitability of its products for any particular purpose, nor does NXP assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation consequential or incidental damages. "Typical" parameters that may be provided in NXP data sheets and/or specifications can and do vary in different applications, and actual performance may vary over time. All operating parameters, including "typicals," must be validated for each customer application by customer's technical experts. NXP does not convey any license under its patent rights nor the rights of others. NXP sells products pursuant to standard terms and conditions of sale, which can be found at the following address: nxp.com/SalesTermsandConditions.

NXP, the NXP logo, Freescale, and the Freescale logo are trademarks of NXP B.V. All other product or service names are the property of their respective owners.
© 2016 NXP B.V.

