


DDCHP-1M0.1G-50-N is a $50\pm 1\text{dB}$ coupling high power dual directional coupler, designed to operate over the 1M-0.1GHz frequency range, with compact size. This model is designed to handle 500W max input power, and also performs with low insertion loss of 0.2dB max and with coupling flatness of $\pm 1\text{dB}$ max, and low VSWR of 1.15 max

Mechanical Outline(Inch/mm):




Environmental Ratings:

Temperature:	-25°C to +71 °C Operating -65 °C to +100 °C Non-Operating
Vibration:	MIL-STD-202F, Method 204D Cond. B
Altitude:	MIL-STD-202F, Method 105C Cond. B
Temperature Cycle:	MIL-STD-202F, Method 107D Cond. A

Specifications:

Coupling:	50±1dB
Frequency:	1M-0.1GHz
Insertion Loss:	0.2dB max
Coupling flatness:	±1dB max
Directivity:	20dB min
Power Handling:	500W max
VSWR:	1.2:1 max
Connectors:	In-Out: N Female Coupling: SMA Female

High Power Dual Directional Coupler DDCHP-1M0.1G-50-N

DRAWN:	DWG NO.:	REV CODE: Rev.1.0	 www.connphy.com sales@connphy.com
CHECKRD:	DATE: 18/04/15	SHEET : 1 OF 1	
ISSUED:	SIZE: A	SCALE : N / A	
			Notes: SPEC ARE SUBJECT TO CHANGE WITHOUT NOTICE.