

## Within Series Adaptor 32\_SMPX-50-0-1/111\_N

### Description

Adaptor plug/plug  
SMPX plug (male) / SMPX plug (male)

Interface standard  
Series SMPX - MIL-STD-348A/326\_DESC 94007/94008



### Technical Data

#### Electrical Data

Impedance 50  $\Omega$   
Interface frequency max. 40 GHz

#### Mechanical Data

Number of matings 500  
Weight 0.0002 kg

#### Environmental Data

Operating temperature °C to °C  
2011/65/EU (RoHS) compliant

#### Material Data

Interface - SMPX plug (male)

Piece Parts	Material	Surface Plating
Centre contact	Copper Beryllium Alloy	Gold Plating (Nickel underplated)
Outer contact	Copper Beryllium Alloy	Gold Plating (Nickel underplated)
Body	Copper Beryllium Alloy	Gold Plating (Nickel underplated)
Insulator	PFA / PTFE	

Interface - SMPX plug (male)

Piece Parts	Material	Surface Plating
Centre contact	Copper Beryllium Alloy	Gold Plating (Nickel underplated)
Outer contact	Copper Beryllium Alloy	Gold Plating (Nickel underplated)
Body	Copper Beryllium Alloy	Gold Plating (Nickel underplated)
Insulator	PFA / PTFE	

### Related Documents

Outline drawing DOU-00013844

### Ordering Information

Single package 32\_SMPX-50-0-1/111\_NE