

Between Series Adaptor 33_BNC-MCX-75-1/1--_N

Description

Adaptor plug/jack
 BNC plug (male) / MCX-75 jack (female)

Interface standards
 Series BNC - Compatible with IEC 61169-8_MIL-STD-348A/301_CECC 22120
 Series MCX-75 - SUHNER-MCX75



Technical Data

Electrical Data

Impedance 75 Ω
 Interface frequency max. 4 GHz

Mechanical Data

Number of matings 500
 Weight 0.0108 kg

Environmental Data

Operating temperature -55 °C to 155 °C
 2011/65/EU (RoHS) compliant

Material Data

Interface - BNC plug (male)

Piece Parts	Material	Surface Plating
Centre contact	Copper Beryllium Alloy	Gold Plating (Nickel underplated)
Outer contact	Brass	SUCOPLATE (R) Plating
Body	Brass	SUCOPLATE (R) Plating
Insulator	PFA / PTFE	
Coupling nut	Brass	SUCOPLATE (R) Plating
Gasket	VMQ (Silicone rubber)	

Interface - MCX-75 jack (female)

Piece Parts	Material	Surface Plating
Centre contact	Copper Beryllium Alloy	Gold Plating (Nickel underplated)
Outer contact	Brass	Gold Plating (Nickel underplated)
Body	Brass	Gold Plating (Nickel underplated)
Insulator	PFA / PTFE	

Related Documents

Catalogue drawing DCA-00014385

Ordering Information

Single package 33_BNC-MCX-75-1/1--_NE